



CORNER


^{EN} Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; suitable for wall or ceiling mounting; with double-sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

□ Corpo illuminante in profilo di alluminio estruso, modello squadrato; nessuna vite visibile; verniciatura a polvere; profilo consegnabile in anticipo; per montaggio a parete o soffitto; con emissione bilaterale; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
fino a 4,290 lm/m
fino a 139 lm/W
L90 / 50000 h
non DIM
High Performance Opal
IP20

Types



Colore



Distribuzione della luce



wall / ceiling
illumination



tunable white
2700 – 6500 K
(optional)




CORNER surface



OPAL | MID LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.8 W	588 mm	3000 K	1810 lm	131 lm/W	0 4 0 - 8 9 5 2 5 1 <input checked="" type="checkbox"/> O
20.7 W	888 mm	3000 K	2720 lm	131 lm/W	0 4 0 - 8 9 5 3 5 1 <input checked="" type="checkbox"/> O
27.6 W	1188 mm	3000 K	3620 lm	131 lm/W	0 4 0 - 8 9 5 4 5 1 <input checked="" type="checkbox"/> O
53.0 W	2358 mm	3000 K	7250 lm	137 lm/W	0 4 0 - 8 9 5 8 5 1 <input checked="" type="checkbox"/> O
67.0 W	3014 mm	3000 K	9340 lm	139 lm/W	0 4 0 - 8 9 5 9 5 1 <input checked="" type="checkbox"/> O



OPAL | HIGH LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.2 W	588 mm	3000 K	2460 lm	122 lm/W	0 4 0 - 8 9 6 2 5 1 <input checked="" type="checkbox"/> O
29.6 W	888 mm	3000 K	3680 lm	124 lm/W	0 4 0 - 8 9 6 3 5 1 <input checked="" type="checkbox"/> O
39.0 W	1188 mm	3000 K	4910 lm	126 lm/W	0 4 0 - 8 9 6 4 5 1 <input checked="" type="checkbox"/> O
76.0 W	2358 mm	3000 K	9820 lm	129 lm/W	0 4 0 - 8 9 6 8 5 1 <input checked="" type="checkbox"/> O
98.0 W	3014 mm	3000 K	12700 lm	130 lm/W	0 4 0 - 8 9 6 9 5 1 <input checked="" type="checkbox"/> O

Order options

COLOUR	<input checked="" type="checkbox"/>
white aluminium RAL 9006	G
pure white RAL 9010	7
jet black RAL 9005	8