


Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
fino a 4.290 lm/m
fino a 139 lm/W
L80 / 50000 h
non DIM
Opal
IP20

Types



Colours

Distribuzione della luce

CORNER

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; suitable for wall or ceiling mounting; with double-sided light beam; opal cover for uniform illumination; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante in profilo di alluminio estruso, modello squadrato; nessuna vite visibile; verniciatura a polvere; profilo consegnabile in anticipo; per montaggio a parete o soffitto; con emissione bilaterale; diffusore opale per un'illuminazione omogenea; LED ad efficienza energetica con elevata resa cromatica

wall / ceiling illumination

tunable white 2700 – 6500 K (optional)



CORNER surface

OPAL | MID LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.8 W	588 mm	3000 K	1810 lm	131 lm/W	040-895251 ◪ O
20.7 W	888 mm	3000 K	2720 lm	131 lm/W	040-895351 ◪ O
27.6 W	1188 mm	3000 K	3620 lm	131 lm/W	040-895451 ◪ O
53.0 W	2358 mm	3000 K	7250 lm	137 lm/W	040-895851 ◪ O
67.0 W	3014 mm	3000 K	9340 lm	139 lm/W	040-895951 ◪ O

OPAL | HIGH LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.2 W	588 mm	3000 K	2460 lm	122 lm/W	040-896251 ◪ O
29.6 W	888 mm	3000 K	3680 lm	124 lm/W	040-896351 ◪ O
39.0 W	1188 mm	3000 K	4910 lm	126 lm/W	040-896451 ◪ O
76.0 W	2358 mm	3000 K	9820 lm	129 lm/W	040-896851 ◪ O
98.0 W	3014 mm	3000 K	12700 lm	130 lm/W	040-896951 ◪ O

Order options

COLOUR ◪	
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G