



DOC

surface


EN Round surface mounted luminaire, housing in die-cast aluminium; central decorative disc made of galvanized sheet steel attached by magnet; surface powder coated; opal cover for completely homogeneous illumination; with increased transmission and diffusion; energy-efficient LEDs with very good colour rendering; degree of protection IP54, with pressure compensation valve; ambient temperatures from -20°C to + 50°C; ø180mm: suitable for through wiring

IT Apparecchio a plafone rotondo, corpo illuminante in alluminio pressofuso; disco decorativo centrale in lamiera d'acciaio zincata fissato a magnete; verniciatura a polvere; diffusore opale per un'illuminazione omogenea; con maggiore trasmissione e diffusione; LED ad efficienza energetica con elevata resa cromatica; protezione IP54, valvola di compens. pressione; temperature ambiente da -20°C a +50°C; ø 180 mm: adatto per cablaggio passante

Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
fino a 104 lm/W
L90 / 50000 h
non DIM
IP54, IK07, IK09

Types




Colore



Distribuzione della luce





DOC 180 surface



OPAL CRI ≥ 80, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.5 W	3000 K	1340 lm	99 lm/W	0 8 8 - 2 7 1 0 5 1 <input checked="" type="checkbox"/>




DOC 360 surface



OPAL CRI ≥ 80, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.8 W	3000 K	2890 lm	104 lm/W	0 8 8 - 2 7 2 0 5 1 <input checked="" type="checkbox"/>



Order options

COLOUR	
grey aluminium RAL 9007	D <input checked="" type="checkbox"/>
pure white RAL 9010	7
jet black RAL 9005	8