



SASSO 60 round

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

IT Faretto a incasso rotondo; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura; incasso possibile in vari telai; a scelta orientabile / fisso simmetrico o asimmetrico caratteristiche di emissione; varianti con emissione simmetrica: emissione precisa con ottica lenticolare di alta qualità; varianti a fascio asimmetrica: riflettore di alta qualità con superficie a micro-faccette e vaporizzata in alluminio; tecnologia COB (Chip on Board) per la massima efficienza (ADJUSTABLE e DOWNLIGHT); assenza di ombre multiple; LED efficienti con alta resa cromatica

Types



Distribuzione della luce



rotatable 360°,
tiltable 30°



wallwasher and
wallwasher
floor inset



glare control
(UGR ≤ 16)



60 mm
recessed depth



Colour Warm
Dimming 1800
- 3000 K



SASSO 60 round downlight



SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.9 W, 36 Vf, 300 mA	2700 K	896 lm	83 lm/W	0 4 8 - 2 6 0 2 9 1 ☒ S
	3000 K	925 lm	85 lm/W	0 4 8 - 2 6 0 2 0 1 ☒ S
	3500 K	945 lm	87 lm/W	0 4 8 - 2 6 0 2 2 1 ☒ S
	4000 K	974 lm	90 lm/W	0 4 8 - 2 6 0 2 1 1 ☒ S

The data values for the luminaire luminous flux may differ for specific order options by -7%. Luminous flux value refers to colour traffic white.

MEDIUM 26°-27°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	793 lm	78 lm/W	0 4 8 - 2 6 0 2 E 1 ☒ M
10.6 W, 36 Vf, 300 mA	2700 K	1050 lm	99 lm/W	0 4 8 - 2 6 0 2 9 1 ☒ M
	3000 K	1090 lm	102 lm/W	0 4 8 - 2 6 0 2 0 1 ☒ M
	3500 K	1110 lm	105 lm/W	0 4 8 - 2 6 0 2 2 1 ☒ M
	4000 K	1140 lm	107 lm/W	0 4 8 - 2 6 0 2 1 1 ☒ M

The data values for the luminaire luminous flux may differ for specific order options by -10%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver

FLOOD 36°-40°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	769 lm	75 lm/W	0 4 8 - 2 6 0 2 E 1 ☒ F
10.6 W, 36 Vf, 300 mA	2700 K	998 lm	94 lm/W	0 4 8 - 2 6 0 2 9 1 ☒ F
	3000 K	1040 lm	97 lm/W	0 4 8 - 2 6 0 2 0 1 ☒ F
	3500 K	1060 lm	100 lm/W	0 4 8 - 2 6 0 2 2 1 ☒ F
	4000 K	1080 lm	102 lm/W	0 4 8 - 2 6 0 2 1 1 ☒ F

The data values for the luminaire luminous flux may differ for specific order options by -14%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver

WIDE FLOOD 56°-57°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.6 W, 36 Vf, 300 mA	2700 K	1050 lm	99 lm/W	0 4 8 - 2 6 0 2 9 1 ☒ W
	3000 K	1090 lm	102 lm/W	0 4 8 - 2 6 0 2 0 1 ☒ W
	3500 K	1110 lm	104 lm/W	0 4 8 - 2 6 0 2 2 1 ☒ W
	4000 K	1130 lm	107 lm/W	0 4 8 - 2 6 0 2 1 1 ☒ W

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver, traffic white.

Order options

COLOUR	
jet black RAL 9005	1 ☒
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9



SASSO 60 round adjustable



SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.9 W, 36 Vf, 300 mA	2700 K	879 lm	81 lm/W	0 4 8 - 2 6 2 2 9 1 ☒ S
	3000 K	908 lm	84 lm/W	0 4 8 - 2 6 2 2 0 1 ☒ S
	3500 K	927 lm	85 lm/W	0 4 8 - 2 6 2 2 2 1 ☒ S
	4000 K	956 lm	88 lm/W	0 4 8 - 2 6 2 2 1 1 ☒ S

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

MEDIUM 26°-27°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	781 lm	76 lm/W	0 4 8 - 2 6 2 2 E 1 ☒ M
10.6 W, 36 Vf, 300 mA	2700 K	1040 lm	98 lm/W	0 4 8 - 2 6 2 2 9 1 ☒ M
	3000 K	1080 lm	102 lm/W	0 4 8 - 2 6 2 2 0 1 ☒ M
	3500 K	1110 lm	104 lm/W	0 4 8 - 2 6 2 2 2 1 ☒ M
	4000 K	1130 lm	106 lm/W	0 4 8 - 2 6 2 2 1 1 ☒ M

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver

FLOOD 36°-41°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	745 lm	73 lm/W	0 4 8 - 2 6 2 2 E 1 ☒ F
10.6 W, 36 Vf, 300 mA	2700 K	992 lm	93 lm/W	0 4 8 - 2 6 2 2 9 1 ☒ F
	3000 K	1030 lm	97 lm/W	0 4 8 - 2 6 2 2 0 1 ☒ F
	3500 K	1050 lm	99 lm/W	0 4 8 - 2 6 2 2 2 1 ☒ F
	4000 K	1070 lm	101 lm/W	0 4 8 - 2 6 2 2 1 1 ☒ F

The data values for the luminaire luminous flux may differ for specific order options by -14%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver

WIDE FLOOD 56°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.6 W, 36 Vf, 300 mA	2700 K	1050 lm	98 lm/W	0 4 8 - 2 6 2 2 9 1 ☒ W
	3000 K	1090 lm	102 lm/W	0 4 8 - 2 6 2 2 0 1 ☒ W
	3500 K	1110 lm	104 lm/W	0 4 8 - 2 6 2 2 2 1 ☒ W
	4000 K	1130 lm	107 lm/W	0 4 8 - 2 6 2 2 1 1 ☒ W

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver, traffic white.

Order options

COLOUR	
jet black RAL 9005	1 ☒
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9



SASSO 60 round wallwasher



WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.1 W, 36 Vf, 250 mA	2700 K	576 lm	71 lm/W	0 4 8 - 2 6 4 1 9 1 ☒ A
	3000 K	626 lm	77 lm/W	0 4 8 - 2 6 4 1 0 1 ☒ A
	3500 K	626 lm	77 lm/W	0 4 8 - 2 6 4 1 2 1 ☒ A
	4000 K	650 lm	80 lm/W	0 4 8 - 2 6 4 1 1 1 ☒ A

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.



SASSO 60 round wallwasher/floor




WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W, 36 Vf, 250 mA	2700 K	1000 lm	113 lm/W	0 4 8 - 2 6 4 1 9 1 ☒ W
	3000 K	1050 lm	118 lm/W	0 4 8 - 2 6 4 1 0 1 ☒ W
	3500 K	1050 lm	118 lm/W	0 4 8 - 2 6 4 1 2 1 ☒ W
	4000 K	1090 lm	123 lm/W	0 4 8 - 2 6 4 1 1 1 ☒ W



Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless


TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/25 mm	traffic white	73-29	0 4 8 - 2 6 9 6 1 1 7

for SASSO 60 round | SPIO 60 downlight




MOUNTING SET trimless for soft acoustic ceilings


COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	25-40 mm	80-25	0 4 8 - 2 6 9 6 1 9 7

**MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm**

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80-40	0 4 8 - 2 6 9 6 3 1 7
jet black	80-40	0 4 8 - 2 6 9 6 3 1 8
white aluminium	80-40	0 4 8 - 2 6 9 6 3 1 G

**MOUNTING SET with trim for soft acoustic ceilings 25-40 mm**


COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80-27	0 4 8 - 2 6 9 6 3 9 7
jet black	80-27	0 4 8 - 2 6 9 6 3 9 8

Mounting accessories (optional)**EXPOSED CONCRETE MOUNTING HOUSING**

COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230-230-162	0 4 8 - 2 6 9 5 2 1 0

**MOUNTING TOOL**

TYPE	COLOUR	L·W·H (mm)	ORDER CODE
for soft acoustic ceilings	traffic black	77-77-35	0 4 8 - 2 6 9 5 9 1 8

**PRIMED CONCRETE MOUNTING HOUSING**

L·W·H (mm)	ORDER CODE
614-307-120	0 4 8 - 2 6 9 5 1 1 0

order mounting set separately


Electrical accessories (required)**POWER SUPPLY PC2, 198-264 V AC**

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
250 mA 10 W non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
250 mA 15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 8
300 mA 13 W non DIM	η 87 %	85-40-22	0 0 2 - 9 0 7 7 1
300 mA 15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 9 0

Electrical accessories (optional)**DIN RAIL LED DRIVER**

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2 × 42W | 48V DC | U OUT 10 - 40V

**DIN RAIL POWER SUPPLY**

L·W·H (mm)	ORDER CODE
72-90-63	0 0 5 - 6 5 2 0 2 1 0

220-240 V AC | 160W | 48V DC constant voltage

POWER SUPPLY PRE-WIRED with junction box PC2, 198-264 V AC

TYPE	EFFICIENCY	ORDER CODE
250 mA 10 W non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A
250 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA 15 W non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
300 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A

POWER SUPPLY with loop through function 15 W, DALI-2, PC2, 198-264 V AC

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 4 7
300 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 7 0

Land Rover Showroom, Hanoi


Vietnam

Lighting Design
kobi lighting studio


Fotografo
Land Rover Hanoi




Prodotti utilizzati




**TWIST 100 1 lamp
recessed**



**SASSO 60 round
recessed 1 lamp**



VARO 110 S



**SASSO 100 round
downlight recessed 1
lamp**



