

SASSO 60 square

recessed 1 lamp

^{EN} Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; choice of fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

^{IT} Faretto a incasso quadrato; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura; incasso possibile in vari telai; a scelta fisso simmetrico o asimmetrico caratteristiche di emissione; varianti con emissione simmetrica: emissione precisa con ottica lenticolare di alta qualità; varianti a fascio asimmetrica: riflettore di alta qualità con superficie a microfacette e vaporizzata in alluminio; tecnologia COB (Chip on Board) per la massima efficienza (DOWNLIGHT); assenza di ombre multiple; LED efficienti con alta resa cromatica

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
colour warm dimming 1800 K -
3000 K
CRI ≥ 90 / 2 SDCM, 3 SDCM
UGR ≤ 13 , UGR ≤ 16 , UGR ≤ 19
fino a 124 lm/W
L80 / 50000 h, L85 / 50000 h,
L90 / 50000 h
DALI-2, non DIM
front IP20, IP40, IP44, back IP20

Types

trim	 48
	 80
trimless	 48
	 63
double trim	 48
	147 x 81

Colore



Set di montaggio



Distribuzione della luce



wallwasher and
wallwasher
floor inset



glare control
(UGR ≤ 16)




60 mm
recessed depth




Colour Warm
Dimming 1800
– 3000 K



CRI ≥ 95 2
SDCM
(optional)



SASSO 60 square downlight



SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.9 W, 36 Vf, 300 mA	2700 K	898 lm	83 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ S
	3000 K	928 lm	85 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ S
	3500 K	947 lm	87 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ S
	4000 K	976 lm	90 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ S

The data values for the luminaire luminous flux may differ for specific order options by -7%. Luminous flux value refers to colour matt silver.

MEDIUM 26°-27°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	814 lm	80 lm/W	0 4 8 - 2 6 1 2 E 1 ☒ M
10.6 W, 36 Vf, 300 mA	2700 K	1070 lm	100 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ M
	3000 K	1110 lm	104 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ M
	3500 K	1130 lm	106 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ M
	4000 K	1160 lm	109 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ M

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

FLOOD 35°-42°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	791 lm	77 lm/W	0 4 8 - 2 6 1 2 E 1 ☒ F
10.6 W, 36 Vf, 300 mA	2700 K	1020 lm	96 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ F
	3000 K	1060 lm	100 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ F
	3500 K	1080 lm	102 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ F
	4000 K	1110 lm	104 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ F

The data values for the luminaire luminous flux may differ for specific order options by -13%. Luminous flux value refers to colour matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver


WIDE FLOOD 57°-58°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.6 W, 36 Vf, 300 mA	2700 K	1070 lm	101 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ W
	3000 K	1110 lm	104 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ W
	3500 K	1130 lm	107 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ W
	4000 K	1160 lm	109 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ W

The data values for the luminaire luminous flux may differ for specific order options by -10%. Luminous flux value refers to colour matt silver.

Order options

COLOUR	
jet black RAL 9005	1 ☒
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9




SASSO 60 square wallwasher



WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.1 W, 36 Vf, 250 mA	2700 K	593 lm	73 lm/W	0 4 8 - 2 6 5 1 9 1 ☒ A
	3000 K	644 lm	80 lm/W	0 4 8 - 2 6 5 1 0 1 ☒ A
	3500 K	644 lm	80 lm/W	0 4 8 - 2 6 5 1 2 1 ☒ A
	4000 K	670 lm	83 lm/W	0 4 8 - 2 6 5 1 1 1 ☒ A

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.




SASSO 60 square wallwasher/floor



WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W, 36 Vf, 250 mA	2700 K	1010 lm	115 lm/W	0 4 8 - 2 6 5 1 9 1 ☒ W
	3000 K	1060 lm	119 lm/W	0 4 8 - 2 6 5 1 0 1 ☒ W
	3500 K	1060 lm	119 lm/W	0 4 8 - 2 6 5 1 2 1 ☒ W
	4000 K	1100 lm	124 lm/W	0 4 8 - 2 6 5 1 1 1 ☒ W

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

Mounting accessories (required)




MOUNTING SET trimless

TYPE	COLOUR	L-W-H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/25 mm	traffic white	72-72-29	0 4 8 - 2 6 9 7 1 1 7



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
traffic white	80-80-21	0 4 8 - 2 6 9 7 3 1 7
jet black	80-80-21	0 4 8 - 2 6 9 7 3 1 8
white aluminium	80-80-21	0 4 8 - 2 6 9 7 3 1 G



Mounting accessories (optional)

PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	0 4 8 - 2 6 9 5 1 1 0
order mounting set separately	

Electrical accessories (required)

POWER SUPPLY PC2, 198-264 V AC


TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
250 mA 10 W non DIM	η 80 %	65·39·20	0 0 2 - 9 0 7 4 2
250 mA 15 W DALI-2	η 87 %	165·29·21	0 0 2 - 9 0 7 4 8
300 mA 13 W non DIM	η 87 %	85·40·22	0 0 2 - 9 0 7 7 1
300 mA 15 W DALI-2	η 87 %	165·29·21	0 0 2 - 9 0 7 9 0

Electrical accessories (optional)

DIN RAIL LED DRIVER



TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36·88·59	0 0 5 - 6 1 2 1 0 3 0
200 - 1050 mA settable const. current 2 × 42 W 48 V DC U OUT 10–40 V		



DIN RAIL POWER SUPPLY

L·W·H (mm)	ORDER CODE
72·90·63	0 0 5 - 6 5 2 0 2 1 0
220-240 V AC 160 W 48 V DC constant voltage	

POWER SUPPLY PRE-WIRED with junction box PC2, 198-264 V AC

TYPE	EFFICIENCY	ORDER CODE
250 mA 10 W non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A
250 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA 15 W non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
300 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A

POWER SUPPLY with loop through function 15 W, DALI-2, PC2, 198-264 V AC

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
250 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 4 7
300 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 7 0

Zeitgeist, Graz

Austria

Architetto

FIPE Architects

Fotografo

Corinna Klug



Prodotti utilizzati



**SASSO 100 square
recessed 1 lamp**



**SASSO 60 square
recessed 1 lamp**



