



SASSO 60 square

recessed 2 lamps

EN Square recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; choice of fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering


IT Faretto a incasso quadrato; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili; verniciatura; con bordo perimetrale; biemissione; a scelta fisso simmetrico o asimmetrico caratteristiche di emissione; varianti con emissione simmetrica: emissione precisa con ottica lenticolare di alta qualità; varianti a fascio asimmetrica: riflettore di alta qualità con superficie a microfaccette e vaporizzata in alluminio; tecnologia COB (Chip on Board) per la massima efficienza (DOWNLIGHT); assenza di ombre multiple; LED efficienti con alta resa cromatica

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
colour warm dimming 1800 K -
3000 K
CRI ≥ 90 / 2 SDCM, 3 SDCM
UGR ≤ 10 , UGR ≤ 13 , UGR ≤ 16 ,
UGR ≤ 19
fino a 124 lm/W
L80 / 50000 h, L85 / 50000 h,
L90 / 50000 h
DALI-2, non DIM
front IP20, IP40, IP44, back IP20

Types

double trim



Colore



Set di montaggio



Distribuzione della luce



wallwasher and
wallwasher
floor inset



glare control
(UGR ≤ 16)





60 mm
recessed depth



Colour Warm
Dimming 1800
– 3000 K



CRI ≥ 95 2
SDCM
(optional)



SASSO 60 square downlight



SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.9 W, 36 Vf, 300 mA	2700 K	2x898 lm	83 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ S
	3000 K	2x928 lm	85 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ S
	3500 K	2x947 lm	87 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ S
	4000 K	2x976 lm	90 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ S

The data values for the luminaire luminous flux may differ for specific order options by -7%. Luminous flux value refers to colour matt silver.

MEDIUM 26°-27°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.2 W, 300 mA	CWD	2x814 lm	80 lm/W	0 4 8 - 2 6 1 2 E 1 ☒ M
2x10.6 W, 36 Vf, 300 mA	2700 K	2x1070 lm	100 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ M
	3000 K	2x1110 lm	104 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ M
	3500 K	2x1130 lm	106 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ M
	4000 K	2x1160 lm	109 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ M

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

FLOOD 35°-42°, CRI ≥ 90



FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.2 W, 300 mA	CWD	2x791 lm	77 lm/W	0 4 8 - 2 6 1 2 E 1 ☒ F
2x10.6 W, 36 Vf, 300 mA	2700 K	2x1020 lm	96 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ F
	3000 K	2x1060 lm	100 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ F
	3500 K	2x1080 lm	102 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ F
	4000 K	2x1110 lm	104 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ F

The data values for the luminaire luminous flux may differ for specific order options by -13%. Luminous flux value refers to colour matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver

WIDE FLOOD 57°-58°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.6 W, 36 Vf, 300 mA	2700 K	2x1070 lm	101 lm/W	0 4 8 - 2 6 1 2 9 1 ☒ W
	3000 K	2x1110 lm	104 lm/W	0 4 8 - 2 6 1 2 0 1 ☒ W
	3500 K	2x1130 lm	107 lm/W	0 4 8 - 2 6 1 2 2 1 ☒ W
	4000 K	2x1160 lm	109 lm/W	0 4 8 - 2 6 1 2 1 1 ☒ W

The data values for the luminaire luminous flux may differ for specific order options by -10%. Luminous flux value refers to colour matt silver.



SASSO 60 square wallwasher



WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x8.1 W, 36 Vf, 250 mA	2700 K	2x593 lm	73 lm/W	0 4 8 - 2 6 5 1 9 1 ☒ A
	3000 K	2x644 lm	80 lm/W	0 4 8 - 2 6 5 1 0 1 ☒ A
	3500 K	2x644 lm	80 lm/W	0 4 8 - 2 6 5 1 2 1 ☒ A
	4000 K	2x670 lm	83 lm/W	0 4 8 - 2 6 5 1 1 1 ☒ A

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white, matt silver.

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9




SASSO 60 square wallwasher/floor




WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x8.9 W, 36 Vf, 250 mA	2700 K	2x1010 lm	115 lm/W	0 4 8 - 2 6 5 1 9 1 ☒ W
	3000 K	2x1060 lm	119 lm/W	0 4 8 - 2 6 5 1 0 1 ☒ W
	3500 K	2x1060 lm	119 lm/W	0 4 8 - 2 6 5 1 2 1 ☒ W
	4000 K	2x1100 lm	124 lm/W	0 4 8 - 2 6 5 1 1 1 ☒ W



Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
traffic white	147-81-35	0 4 8 - 2 6 9 9 3 1 7
jet black	147-81-35	0 4 8 - 2 6 9 9 3 1 8
white aluminium	147-81-35	0 4 8 - 2 6 9 9 3 1 G

Electrical accessories (required)

POWER SUPPLY PC2, 198-264 V AC

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA 10 W non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
250 mA 15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 8
300 mA 13 W non DIM	η 87 %	85-40-22	0 0 2 - 9 0 7 7 1
300 mA 15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 9 0


Electrical accessories (optional)



DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10–40 V



DIN RAIL POWER SUPPLY

L-W-H (mm)	ORDER CODE
72-90-63	0 0 5 - 6 5 2 0 2 1 0

220-240 V AC | 160 W | 48 V DC constant voltage

Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

POWER SUPPLY PRE-WIRED with junction box PC2, 198-264 V AC

TYPE	EFFICIENCY	ORDER CODE
250 mA 10 W non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A
250 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA 15 W non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
300 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A

POWER SUPPLY with loop through function 15 W, DALI-2, PC2, 198-264 V AC

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 4 7
300 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 7 0