

## LINEA

system


<sup>EN</sup> Luminaire housing and front cover from extruded aluminium profile, angular version; no visible screws; designed for continuous lighting systems, 90° angle connectors for flexible system design; surface powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; HPO (High Performance Opal) cover for uniform illumination; or with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); energy-efficient LEDs with very good colour rendering; optionally JUST 26 spotlight module can be installed

<sup>IT</sup> Corpo illuminante e copertura frontale in profilo di alluminio estruso, modello squadrato; nessuna vite visibile; predisposto per file continue, giunto angolare a 90° per composizioni flessibili; verniciatura a polvere; montaggio a parete; distribuzione diretta/indiretta equilibrata per una luminosità omogenea del soffitto o parete; diffusore HPO (High Performance Opal) per un'illuminazione omogenea; o con lente asimmetrica appositamente tarata per livelli di illuminazione omogenei (montaggio per l'illum. pavimento o soffitto a scelta); LED ad efficienza energetica con elevata resa cromatica; inserito faretto JUST 26 montato in opzione


### Quickinfo

3000 K, 4000 K, tunable white  
2700 - 5000 K  
CRI ≥ 90, CRI ≥ 97 / 3 SDCM  
(initial MacAdam)  
fino a ↓ 4,020 lm/l / 4,770 lm  
fino a 125 lm/W  
L85 / 50000 h, L95 / 50000 h  
DALI-2, non DIM  
High Performance Opal, High  
Performance Opal / Asymmetric  
IP20 / classe isolamento 1 /  
220-240 V

### Types



### Distribuzione della luce



CRI ≥ 98  
XPECTRUM  
(optional)



## LINEA wall system



### OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W	306 mm	3000 K	↓428/±509 lm	105 lm/W	0 5 8 - 6 1 4 1 5 <input checked="" type="checkbox"/> A A
		4000 K	↓472/±562 lm	116 lm/W	0 5 8 - 6 1 4 1 6 <input checked="" type="checkbox"/> A A
17.6 W	606 mm	3000 K	↓881/±1050 lm	110 lm/W	0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> A A
		4000 K	↓972/±1160 lm	121 lm/W	0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> A A
34.0 W	1206 mm	3000 K	↓1760/±2090 lm	113 lm/W	0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> A A
		4000 K	↓1940/±2310 lm	125 lm/W	0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> A A
39.0 W	1206 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2390 lm	113 lm/W	0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> A A
68.0 W	2406 mm	3000 K	↓3520/±4190 lm	113 lm/W	0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> A A
		4000 K	↓3890/±4620 lm	125 lm/W	0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> A A
76.0 W	2406 mm	↓ tunable w./ ±2700 K - 5000 K	↓4020/±4770 lm	116 lm/W	0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> A A



### OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W	306 mm	3000 K	↓428/±428 lm	96 lm/W	0 5 8 - 6 1 4 1 5 <input checked="" type="checkbox"/> A H
		4000 K	↓472/±472 lm	106 lm/W	0 5 8 - 6 1 4 1 6 <input checked="" type="checkbox"/> A H
17.6 W	606 mm	3000 K	↓881/±881 lm	100 lm/W	0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> A H
		4000 K	↓972/±972 lm	110 lm/W	0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> A H
34.0 W	1206 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> A H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> A H
39.0 W	1206 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> A H
68.0 W	2406 mm	3000 K	↓3520/±3520 lm	104 lm/W	0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> A H
		4000 K	↓3890/±3890 lm	114 lm/W	0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> A H
76.0 W	2406 mm	↓ tunable w./ ±2700 K - 5000 K	↓4020/±4020 lm	106 lm/W	0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> A H




## LINEA inner corner wall system



### OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	633 mm	3000 K	↓1760/±2090 lm	113 lm/W	0 5 8 - 6 1 1 1 5 <input checked="" type="checkbox"/> A A
		4000 K	↓1940/±2310 lm	125 lm/W	0 5 8 - 6 1 1 1 6 <input checked="" type="checkbox"/> A A
39.0 W	633 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2390 lm	113 lm/W	0 5 8 - 6 1 1 1 D 3 <input checked="" type="checkbox"/> A A



### OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	633 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 1 1 5 <input checked="" type="checkbox"/> A H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 1 1 6 <input checked="" type="checkbox"/> A H
39.0 W	633 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 1 1 D 3 <input checked="" type="checkbox"/> A H

## Order options

CONTROL		COLOUR		MOUNTING	
non DIM	1	pure white RAL 9010	7	spotlight left	B
DALI-2	3	jet black RAL 9005	8	spotlight right	C




## LINEA outer corner wall system



### OPAL / ASYMMETRIC CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	637 mm	3000 K	↓1760/±2090 lm	113 lm/W	0 5 8 - 6 1 1 2 5 <input checked="" type="checkbox"/> A A
		4000 K	↓1940/±2310 lm	125 lm/W	0 5 8 - 6 1 1 2 6 <input checked="" type="checkbox"/> A A
39.0 W	637 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2390 lm	113 lm/W	0 5 8 - 6 1 1 2 D 3 <input checked="" type="checkbox"/> A A



### OPAL / OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	637 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 1 2 5 <input checked="" type="checkbox"/> A H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 1 2 6 <input checked="" type="checkbox"/> A H
39.0 W	637 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 1 2 D 3 <input checked="" type="checkbox"/> A H




## LINEA 1 spotlight wall system



### OPAL / OPAL | 1 SPOTLIGHT 30°, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.6 W	706 mm	3000 K	↓881/±881 lm	100 lm/W	0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	↓972/±972 lm	110 lm/W	0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
34.0 W	1306 mm	3000 K	↓1760/±1760 lm	104 lm/W	0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	↓1940/±1940 lm	114 lm/W	0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
39.0 W	1306 mm	↓ tunable w./ ±2700 K - 5000 K	↓2010/±2010 lm	103 lm/W	0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
68.0 W	2506 mm	3000 K	↓3520/±3520 lm	104 lm/W	0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	↓3890/±3890 lm	114 lm/W	0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
76.0 W	2506 mm	↓ tunable w./ ±2700 K - 5000 K	↓4020/±4020 lm	106 lm/W	0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H



spotlight 1 x 2,6 W / 159 lm only with 3000 K

## Mounting accessories (optional)



### END CAPS 1 pair

L-W-H (mm)  
40-100-12

ORDER CODE  
0 5 0 - 2 5 4 0 1 0



### LINEAR CONNECTOR

TYPE  
1 piece  
10 pieces

L-W (mm)  
60-38

ORDER CODE  
0 5 0 - 2 5 5 1 1 0 0  
0 5 0 - 2 5 5 1 1 0 0 · 1 0

## Order options

CONTROL		COLOUR		MOUNTING	
non DIM	1	pure white RAL 9010	7	spotlight left	B
DALI-2	3	jet black RAL 9005	8	spotlight right	C

**Electrical accessories (optional)****THROUGH WIRE****TYPE**3×1.5mm<sup>2</sup> | 10 pieces | non DIM5×1.5mm<sup>2</sup> | 10 pieces | DALI-2**ORDER CODE**

0 0 4 - 9 0 0 0 3

0 0 4 - 9 0 0 0 5

**Order options**

<b>CONTROL</b>		<b>COLOUR</b>	<input checked="" type="checkbox"/>	<b>MOUNTING</b>	
non DIM	1	pure white RAL 9010	7	spotlight left	B
DALI-2	3	jet black RAL 9005	8	spotlight right	C