

## UNICO wall

surface


<sup>EN</sup> Rectangular wall surface mounted multi-uplight made of aluminium; equipped with one light inset (1 LAMP) / two (2 LAMPS) / four (4 LAMPS) light insets; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

Multi-uplight rettangolare in alluminio a plafone; con un inserto luminoso (1 LAMP) / due ins. lum. (2 LAMPS) / quattro ins. lum. (4 LAMPS); corpo illuminante montabile ad appoggio senza attrezzi su piastra di montaggio tramite blocco di sicurezza; convertitore integrato nel corpo illuminante; verniciatura a polvere; riflettore di alta qualità con superficie a microfacette e vaporizzata in alluminio; distribuzione equilibrata per una luminosità omogenea del soffitto o parete; LED high power a risparmio energetico con ottima resa cromatica; apparecchio per cabbaggio passante

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI ≥ 90 / 3 SDCM (initial MacAdam)  
 fino a 48 lm/W  
 L80 / 50000 h, L90 / 50000 h  
 DALI-2, non DIM  
 IP20

### Types



### Colore



### Distribuzione della luce



homogeneous ceiling illumination



safety glass for dust protection




### UNICO wall 1 lamp surface



#### WIDE FLOOR CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.8 W	2700 K	220 lm	38 lm/W	0 9 0 - 0 L 1 4 1 T <input checked="" type="checkbox"/> 0 0 1
	3000 K	235 lm	41 lm/W	0 9 0 - 0 L 1 5 1 T <input checked="" type="checkbox"/> 0 0 1
	4000 K	244 lm	42 lm/W	0 9 0 - 0 L 1 6 1 T <input checked="" type="checkbox"/> 0 0 1




### UNICO wall 2 lamps surface



#### WIDE FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.3 W	2700 K	650 lm	38 lm/W	0 9 0 - 0 L 2 4 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	3000 K	693 lm	40 lm/W	0 9 0 - 0 L 2 5 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	4000 K	744 lm	43 lm/W	0 9 0 - 0 L 2 6 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1




### UNICO wall 4 lamps surface



#### WIDE FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.1 W	2700 K	1230 lm	42 lm/W	0 9 0 - 0 L 4 4 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	3000 K	1310 lm	45 lm/W	0 9 0 - 0 L 4 5 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1
	4000 K	1410 lm	48 lm/W	0 9 0 - 0 L 4 6 4 <input checked="" type="checkbox"/> T <input checked="" type="checkbox"/> 0 0 1



#### Order options

CONTROL		COLOUR	
non DIM	1	jet black RAL 9005	B
DALI-2	3	white aluminium RAL 9006	G
		traffic white RAL 9016	W