



UNICO Q1 sensor

recessed

^{EN} UNICO Q1 sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; clank-free

^{IT} UNICO Q1 sensor; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili; montaggio elettrico semplice grazie a collegamenti a spina a prova di polarizzazione inversa; per soffitti di spessore 2-25 mm; verniciatura a polvere; incasso possibile in vari telai; senza distorsione

Quickinfo

DALI-2 ESSENTIAL sensor,
DALI-2 SENSE sensor
front IP20

Types

trim



□ 63

trimless



□ 47

Colore



Set di montaggio



Distribuzione della luce



Data
Monitoring


DiiA[®] standards
251, 252, 253



one luminaire
multiple scenes



plug / socket
connector




black & gold
reflector
(optional)



tunable white
2700 - 5000 K
(optional)



UNICO Q1 sensor essential



jet black, DALI-2 ESSENTIAL sensor

ORDER CODE

0 9 0 - 7 Q 1 0 0 0 0



UNICO Q1 sensor sense




jet black, DALI-2 SENSE sensor

ORDER CODE

0 9 0 - 7 Q 1 0 0 1 0

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS

12.5/15/20/25 mm

L·W·H (mm)

47·47·47

ORDER CODE

0 9 0 - 7 Q 1 0 1 0 0

for UNICO Q1



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR

jet black

L·W·H (mm)

63·63·30

ORDER CODE

0 9 0 - 7 Q 1 0 2 0 B

traffic white

63·63·30

0 9 0 - 7 Q 1 0 2 0 W

for UNICO Q1

Order options

COLOUR

jet black

RAL 9005

traffic white

RAL 9016