

Quickinfo

3000 K, 4000 K
CRI ≥ 90, CRI ≥ 97 / 3 SDCM (initial MacAdam)
fino a ↓ 8.950 lm / ↑ 8.950 lm
fino a 14.900 lm/m
fino a 121 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2
Linear Prismatic
IP20

Types

horizontal mounting



vertical mounting



Colours


Distribuzione della luce

VITA


wall

EN Luminaire housing, mounting channel and front cover from extruded aluminium profile, angular version; extremely slim luminaire housing (only 25 mm), for direct/indirect radiation characteristic; no visible screws; surface anodised; suitable for wall mounting; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for direct or indirect light component for optimised light control and homogeneous illumination; lighting modules in aluminium, powder coated; CRI ≥ 90 or XPECTRUM; incl. 2 converters for separate control of the direct/indirect light component; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante, canale di montaggio e copertura frontale in profilo di alluminio estruso, modello squadrato; corpo dell'apparecchio estremamente sottile (solo 25 mm), per un fascio di luce diretto/indiretto; nessuna vite visibile; superficie anodizzata; montaggio a parete; inserti luminosi con riflettori asimmetrici lucidi appositamente calcolati, cover prismatiche lineari incl. pellicola con diversa distribuzione della luce per la componente diretta o indiretta della luce, per un controllo della luce ottimizzato e un'illuminazione omogenea; inserti luminosi in alluminio verniciato a polvere; CRI ≥ 90 o XPECTRUM; incl. 2 convertitori per il controllo separato della componente della luce diretta/indiretta; LED ad efficienza energetica con elevata resa cromatica



system solution




CRI ≥ 98
XPECTRUM



VITA wall horizontal mounting

CRI ≥97 | 220-240 V | 2 ADDR. | X-PERT | X-PERT

LINEAR PRISMATIC | DIRECT / INDIRECT anodised aluminium, DALI-2



SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
123.0 W	1013 mm	3000 K	90	↧7230/↥7230 lm	118 lm/W	0 9 9 - 9 1 3 6 0 3 6 A
			97	↧5740/↥5740 lm	93 lm/W	0 9 9 - 9 1 3 6 Y 3 6 A
		4000 K	90	↧7460/↥7460 lm	121 lm/W	0 9 9 - 9 1 3 6 1 3 6 A
			97	↧5850/↥5850 lm	95 lm/W	0 9 9 - 9 1 3 6 Z 3 6 A
148.0 W	1213 mm	3000 K	90	↧8670/↥8670 lm	117 lm/W	0 9 9 - 9 1 3 7 0 3 6 A
			97	↧6890/↥6890 lm	93 lm/W	0 9 9 - 9 1 3 7 Y 3 6 A
		4000 K	90	↧8950/↥8950 lm	121 lm/W	0 9 9 - 9 1 3 7 1 3 6 A
			97	↧7020/↥7010 lm	95 lm/W	0 9 9 - 9 1 3 7 Z 3 6 A


CRI ≥ 97 XPECTRUM



VITA wall vertical mounting

CRI ≥97 | 220-240 V | 2 ADDR. | X-PERT | X-PERT

LINEAR PRISMATIC | DIRECT / INDIRECT anodised aluminium, DALI-2



SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
123.0 W	1013 mm	3000 K	90	↧7230/↥7230 lm	118 lm/W	0 9 9 - 9 1 6 6 0 3 6 A
			97	↧5740/↥5740 lm	93 lm/W	0 9 9 - 9 1 6 6 Y 3 6 A
		4000 K	90	↧7460/↥7460 lm	121 lm/W	0 9 9 - 9 1 6 6 1 3 6 A
			97	↧5850/↥5850 lm	95 lm/W	0 9 9 - 9 1 6 6 Z 3 6 A
148.0 W	1213 mm	3000 K	90	↧8670/↥8670 lm	117 lm/W	0 9 9 - 9 1 6 7 0 3 6 A
			97	↧6890/↥6890 lm	93 lm/W	0 9 9 - 9 1 6 7 Y 3 6 A
		4000 K	90	↧8950/↥8950 lm	121 lm/W	0 9 9 - 9 1 6 7 1 3 6 A
			97	↧7020/↥7010 lm	95 lm/W	0 9 9 - 9 1 6 7 Z 3 6 A

CRI ≥ 97 XPECTRUM