

Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 22, UGR ≤ 25
fino a ↓ 10.300 lm / ↑ 5.800 lm
fino a 137 lm/W
L90 / 100000 h
Cover: Opal
DALI-2
IP20

Types



Colours



Distribuzione della luce



MINO 60 S CIRCLE

suspended

EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; flat design luminaire housing; surface powder coated; pendant fitting with cable suspension, alternatively with canopy central; height adjustment without tools; incl. feed (black or white); converter included in canopy; opal cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante circolare in profilo di alluminio estruso rullato e senza punti di saldatura; forma piatta; verniciatura a polvere; sospeso con cavo a sospensione, a scelta con rosone centrale; regolazione altezza senza utensili; incl. cavo di alimentazione (nero o bianco); convertitore integrato nel rosone; diffusore opale per un'illuminazione omogenea; rifrattore in PMMA a microprismi incl. pellicola di diffusione per ridurre la luminanza mantenendo l'illuminazione omogenea; in opzione con emissione diretta/indiretta per ulteriore accentuazione del soffitto e migliore comfort visivo; LED ad efficienza energetica con elevata resa cromatica



DiiA® standards 251, 252, 253



direct / indirect illumination







*direct/indirect version



*direct/indirect version

MINO 60 S CIRCLE 1000 suspended

CRI ≥ 80 | 220-240 V | 1-2 ADDR. | X-PERT | X-PERT

OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
59.0 W	3000 K	6860 lm	116 lm/W	034-7ơ1253◪H
	4000 K	7300 lm	124 lm/W	034-7ơ1263◪H

OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
79.0 W	3000 K	↧6860/↥3120 lm	126 lm/W	034-7ơ1353◪H
	4000 K	↧7300/↥3550 lm	137 lm/W	034-7ơ1363◪H







*direct/indirect version



*direct/indirect version

MINO 60 S CIRCLE 1500 suspended

CRI ≥ 80 | UGR ≤22 | 220-240 V | 1-5 ADDR. | X-PERT | X-PERT

OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
83.0 W	3000 K	9630 lm	116 lm/W	034-7ơ1053◪H
	4000 K	10300 lm	124 lm/W	034-7ơ1063◪H

OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
119.0 W	3000 K	↧9630/↥5100 lm	124 lm/W	034-7ơ1153◪H
	4000 K	↧10300/↥5800 lm	135 lm/W	034-7ơ1163◪H

Order options

MOUNTING	ơ
cable 1500 mm	2
cable 1500 mm / canopy central	4

COLOUR	◪
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G
special colours	X

Dentsu Aegis Network, Zurich

Svizzera

Architetto
Büronauten AG

Lighting Design
Caduff Socker

Fotografo
Z. Gataric Fotografie



Prodotti utilizzati



MINO 60 CIRCLE suspended



TULA suspended



TULA MOVE IT 25 / 25 S / 45



MINO 60 S CIRCLE suspended

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com







