



## MICRO 10

recessed


<sup>EN</sup> Round recessed spotlight in aluminium; surface lacquered; high quality lens system; precise radiation characteristic; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

▮ Faretto da incasso rotondo in alluminio; verniciatura; ottica lenticolare di qualità; emissione precisa; LED ad efficienza energetica con elevata resa cromatica; montaggio senza attrezzi tramite connettore con innesto rapido a baionetta; convertitore premontato e pronto all'uso; convertitore da ordinare separatamente

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  95 / 3 SDCM (initial MacAdam)  
 fino a 99 lm/W  
 L80 / 50000 h, L85 / 50000 h  
 excl. driver  
 IP20

### Types



### Colore



### Distribuzione della luce



CRI  $\geq$  95, R9  $\geq$  90

**MICRO 10** recessed**SPOT** 18°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W, 350 mA	3000 K	61 lm	60 lm/W	0 1 1 - 8 1 0 0 0 1 <input checked="" type="checkbox"/> S
1.1 W, 350 mA	4000 K	67 lm	63 lm/W	0 1 1 - 8 1 0 0 1 1 <input checked="" type="checkbox"/> S

light inset incl. connection cable with socket 0.5 m

**MEDIUM** 30°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.9 W, 350 mA	3000 K	92 lm	97 lm/W	0 1 1 - 8 1 0 0 0 1 <input checked="" type="checkbox"/> M
1.0 W, 350 mA	4000 K	100 lm	99 lm/W	0 1 1 - 8 1 0 0 1 1 <input checked="" type="checkbox"/> M

light inset incl. connection cable with socket 0.5 m

**FLOOD** 39°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.9 W, 350 mA	3000 K	93 lm	98 lm/W	0 1 1 - 8 1 0 0 0 1 <input checked="" type="checkbox"/> F
1.0 W, 350 mA	4000 K	101 lm	99 lm/W	0 1 1 - 8 1 0 0 1 1 <input checked="" type="checkbox"/> F

light inset incl. connection cable with socket 0.5 m

**Electrical mounting accessories (optional)****EXTENSION CABLE** 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 1 2 0
2000 mm	0 1 1 - 9 2 2 1 1 4 0
4000 mm	0 1 1 - 9 2 2 1 1 8 0

**Electrical accessories (optional)****POWER SUPPLY EU** 350 mA

TYPE	L-W-H (mm)	ORDER CODE
non DIM	115-19-34	0 1 1 - 9 2 1 3 1 1 0
DALI-2	145-33-21	0 1 1 - 9 2 1 3 1 3 0

incl. power cable 2 m + connection cable with plug 1 m

**POWER SUPPLY UL** 350 mA, 42 W, 90-277 V AC, PC2

EFFICIENCY	L-W-H (mm)	ORDER CODE
η 89 %	131-43-30	0 1 1 - 9 2 7 3 1 1 0
η 89 %		0 1 1 - 9 2 9 3 1 1 0

**CONNECTION CABLE** 1 × open / 1 × top plug

FEEDER LENGTH	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 6 2 0

**Order options**

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> 6
tar black RAL 9021	8

**SPLITTER SERIAL**

<b>TYPE</b>	<b>L·W·H (mm)</b>	<b>ORDER CODE</b>
3 × socket / 1 × plug	38·30·10	0 1 1 - 9 2 2 8 3 0 0
6 × socket / 1 × plug	55·32·10	0 1 1 - 9 2 2 8 6 0 0

**Order options**

<b>COLOUR</b>	<input checked="" type="checkbox"/>
white aluminium RAL 9006	6
tar black RAL 9021	8