






Quickinfo

3000 K, 4000 K
CRI ≥ 95 / 3 SDCM (initial MacAdam)
fino a 106 lm/W
L80 / 50000 h, L85 / 50000 h
excl. driver
IP20

Types



Colours

Distribuzione della luce

STADIO 10

semi-recessed

EN Cylindrical semi-recessed miniature spotlight made of aluminium; surface lacquered; spotlight head rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

IT Faretto miniaturizzato cilindrico in alluminio con montaggio a semincasso; verniciatura; testa del faretto ruotabile e orientabile; ottica lenticolare di qualità; curva fotometrica precisa con diversi angoli di emissione; LED ad efficienza energetica con elevata resa cromatica; montaggio senza attrezzi tramite connettore con innesto rapido a baionetta; convertitore premontato e pronto all'uso; convertitore da ordinare separatamente



CRI ≥ 95, R9 ≥ 90




360° rotatable, 90° tiltable



plug & play





STADIO 10 semi-recessed

90°
360°
CRI ≥ 95
III
DALI 1 ADDR.
X-PERT

SPOT 18°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W, 220 mA	3000 K	44 lm	71 lm/W	0 1 1 - 8 0 0 0 0 1 ◪ S
	4000 K	48 lm	75 lm/W	0 1 1 - 8 0 0 0 1 1 ◪ S

light inset incl. connection cable with plug 0.5 m

MEDIUM 30°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W, 220 mA	3000 K	60 lm	104 lm/W	0 1 1 - 8 0 0 0 0 1 ◪ M
	4000 K	65 lm	105 lm/W	0 1 1 - 8 0 0 0 1 1 ◪ M

light inset incl. connection cable with plug 0.5 m

FLOOD 39°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.6 W, 220 mA	3000 K	60 lm	105 lm/W	0 1 1 - 8 0 0 0 0 1 ◪ F
	4000 K	66 lm	106 lm/W	0 1 1 - 8 0 0 0 1 1 ◪ F

light inset incl. connection cable with plug 0.5 m

Electrical mounting accessories

EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 1 2 0
2000 mm	0 1 1 - 9 2 2 1 1 4 0
4000 mm	0 1 1 - 9 2 2 1 1 8 0

Electrical accessories

POWER SUPPLY EU 220 mA

TYPE	L·W·H (mm)	ORDER CODE
non DIM	115·19·34	0 1 1 - 9 2 1 1 2 1 0
DALI-2	145·33·21	0 1 1 - 9 2 1 1 1 3 0

incl. power cable 2 m + connection cable with socket 1 m

POWER SUPPLY UL 220 mA, 42 W, 90-277 V AC, PC2

EFFICIENCY	L·W·H (mm)	ORDER CODE
η 89 %	131·43·30	0 1 1 - 9 2 7 1 1 1 0
η 89 %		0 1 1 - 9 2 9 1 1 1 0

CONNECTION CABLE 1 × open / 1 × top plug

FEEDER LENGTH	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 6 2 0

Order options

COLOUR	◪
white aluminium RAL 9006	6
tar black RAL 9021	8

NOTE

Products from the Showcase Lighting range are excluded from returns.

SPLITTER SERIAL

TYPE	L·W·H (mm)	ORDER CODE
3 × socket / 1 × plug	38·30·10	011-922830 0
6 × socket / 1 × plug	55·32·10	011-922860 0

Order options

NOTE

Products from the Showcase Lighting range are excluded from returns.