



FINA SUPPORT lead

standing system


EN Miniature rectangular lamp made of aluminium; angular design; surface lacquered; plug and play electrical connector system for tool-less mounting; different mechanical and electrical poles available; for flexible system design; with specially computed foil for asymmetrical light distribution; light inset rotatable; energy-efficient LEDs with very good colour rendering; converter plug and play; converter separately available

IT Lampada rettangolare miniaturizzata in alluminio; design squadrato; verniciatura; montaggio senza attrezzi tramite connettore con innesto rapido a baionetta; disponibili diversi pali (Pole) meccanici ed elettrici; per composizioni flessibili; con pellicola appositamente tarata per una distribuzione asimmetrica della luce; unità luminosa ruotabile; LED ad efficienza energetica con elevata resa cromatica; convertitore premontato e pronto all'uso; convertitore da ordinare separatamente

Quickinfo

3000 K, 3500 K, 4000 K
CRI ≥ 97 / 3 SDCM (initial MacAdam)
fino a 1.480 lm/m
fino a 93 lm/W
L85 / 50000 h
excl. driver
IP20

Types



Colours



Distribuzione della luce




CRI ≥ 95 , R9 ≥ 90




seamless design




360° tiltable



light-directing foil



FINA SUPPORT lead standing system




ASYMMETRIC CRI ≥ 97, excl. driver

FIXTURE	LENGTH	LUM. FLUX	ORDER CODE
1.5 W	100 mm	96 lm	0 1 1 - 1 2 0 1 :: 1 ▣ A
2.0 W	135 mm	142 lm	0 1 1 - 1 2 9 A C :: 1 ▣ A
2.7 W	170 mm	189 lm	0 1 1 - 1 2 9 A D :: 1 ▣ A
3.3 W	205 mm	236 lm	0 1 1 - 1 2 9 A E :: 1 ▣ A
3.6 W	200 mm	255 lm	0 1 1 - 1 2 0 2 :: 1 ▣ A
4.0 W	240 mm	283 lm	0 1 1 - 1 2 9 A F :: 1 ▣ A
4.7 W	275 mm	330 lm	0 1 1 - 1 2 9 A G :: 1 ▣ A
5.3 W	310 mm	378 lm	0 1 1 - 1 2 9 A H :: 1 ▣ A
6.0 W	345 mm	425 lm	0 1 1 - 1 2 9 A I :: 1 ▣ A
6.7 W	380 mm	472 lm	0 1 1 - 1 2 9 A J :: 1 ▣ A
7.3 W	400 mm	511 lm	0 1 1 - 1 2 0 3 :: 1 ▣ A
7.4 W	415 mm	519 lm	0 1 1 - 1 2 9 A K :: 1 ▣ A
8.0 W	450 mm	566 lm	0 1 1 - 1 2 9 A L :: 1 ▣ A
8.7 W	485 mm	614 lm	0 1 1 - 1 2 9 A M :: 1 ▣ A
9.4 W	520 mm	661 lm	0 1 1 - 1 2 9 A N :: 1 ▣ A
10.0 W	555 mm	708 lm	0 1 1 - 1 2 9 A O :: 1 ▣ A
10.6 W	590 mm	755 lm	0 1 1 - 1 2 9 A P :: 1 ▣ A
11.4 W	625 mm	802 lm	0 1 1 - 1 2 9 A Q :: 1 ▣ A
11.6 W	600 mm	818 lm	0 1 1 - 1 2 0 4 :: 1 ▣ A
12.0 W	660 mm	850 lm	0 1 1 - 1 2 9 A R :: 1 ▣ A
12.7 W	695 mm	897 lm	0 1 1 - 1 2 9 A S :: 1 ▣ A
13.4 W	730 mm	944 lm	0 1 1 - 1 2 9 A T :: 1 ▣ A
14.0 W	765 mm	991 lm	0 1 1 - 1 2 9 A U :: 1 ▣ A
14.6 W	800 mm	1020 lm	0 1 1 - 1 2 0 5 :: 1 ▣ A
15.3 W	835 mm	1090 lm	0 1 1 - 1 2 9 A W :: 1 ▣ A
16.1 W	870 mm	1130 lm	0 1 1 - 1 2 9 A X :: 1 ▣ A
16.7 W	905 mm	1180 lm	0 1 1 - 1 2 9 A Y :: 1 ▣ A
17.3 W	940 mm	1230 lm	0 1 1 - 1 2 9 A Z :: 1 ▣ A
18.1 W	975 mm	1270 lm	0 1 1 - 1 2 9 B A :: 1 ▣ A
18.2 W	1000 mm	1280 lm	0 1 1 - 1 2 0 6 :: 1 ▣ A
18.7 W	1010 mm	1320 lm	0 1 1 - 1 2 9 B B :: 1 ▣ A
19.4 W	1045 mm	1370 lm	0 1 1 - 1 2 9 B C :: 1 ▣ A
20.1 W	1080 mm	1420 lm	0 1 1 - 1 2 9 B D :: 1 ▣ A
20.7 W	1115 mm	1460 lm	0 1 1 - 1 2 9 B E :: 1 ▣ A
21.4 W	1150 mm	1510 lm	0 1 1 - 1 2 9 B F :: 1 ▣ A
21.8 W	1200 mm	1530 lm	0 1 1 - 1 2 0 7 :: 1 ▣ A


The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour temperature 4000 K, 3500 K. Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions

Order options

WIDTH	W	WIDTH	W	COLOUR TEMPERATURE	::	COLOUR	▣
20 mm	1	95 mm	7	3000 K	0	white aluminium RAL 9006	6
35 mm	4	100 mm	8	4000 K	1	tar black RAL 9021	8
50 mm	5			3500 K	2		
85 mm	6						



FINA SUPPORT lead 30° standing system



ASYMMETRIC CRI ≥ 97, excl. driver


FIXTURE	LENGTH	LUM. FLUX	ORDER CODE
1.5 W	100 mm	96 lm	0 1 1 - 1 3 0 1 : 1 ☒ A
2.0 W	135 mm	142 lm	0 1 1 - 1 3 9 A C : 1 ☒ A
2.7 W	170 mm	189 lm	0 1 1 - 1 3 9 A D : 1 ☒ A
3.3 W	205 mm	236 lm	0 1 1 - 1 3 9 A E : 1 ☒ A
3.6 W	200 mm	255 lm	0 1 1 - 1 3 0 2 : 1 ☒ A
4.0 W	240 mm	283 lm	0 1 1 - 1 3 9 A F : 1 ☒ A
4.7 W	275 mm	330 lm	0 1 1 - 1 3 9 A G : 1 ☒ A
5.3 W	310 mm	378 lm	0 1 1 - 1 3 9 A H : 1 ☒ A
6.0 W	345 mm	425 lm	0 1 1 - 1 3 9 A I : 1 ☒ A
6.7 W	380 mm	472 lm	0 1 1 - 1 3 9 A J : 1 ☒ A
7.3 W	400 mm	511 lm	0 1 1 - 1 3 0 3 : 1 ☒ A
7.4 W	415 mm	519 lm	0 1 1 - 1 3 9 A K : 1 ☒ A
8.0 W	450 mm	566 lm	0 1 1 - 1 3 9 A L : 1 ☒ A
8.7 W	485 mm	614 lm	0 1 1 - 1 3 9 A M : 1 ☒ A
9.4 W	520 mm	661 lm	0 1 1 - 1 3 9 A N : 1 ☒ A
10.0 W	555 mm	708 lm	0 1 1 - 1 3 9 A O : 1 ☒ A
10.6 W	590 mm	755 lm	0 1 1 - 1 3 9 A P : 1 ☒ A
11.4 W	625 mm	802 lm	0 1 1 - 1 3 9 A Q : 1 ☒ A
11.6 W	600 mm	818 lm	0 1 1 - 1 3 0 4 : 1 ☒ A
12.0 W	660 mm	850 lm	0 1 1 - 1 3 9 A R : 1 ☒ A
12.7 W	695 mm	897 lm	0 1 1 - 1 3 9 A S : 1 ☒ A
13.4 W	730 mm	944 lm	0 1 1 - 1 3 9 A T : 1 ☒ A
14.0 W	765 mm	991 lm	0 1 1 - 1 3 9 A U : 1 ☒ A
14.6 W	800 mm	1020 lm	0 1 1 - 1 3 0 5 : 1 ☒ A
15.3 W	835 mm	1090 lm	0 1 1 - 1 3 9 A W : 1 ☒ A
16.1 W	870 mm	1130 lm	0 1 1 - 1 3 9 A X : 1 ☒ A
16.7 W	905 mm	1180 lm	0 1 1 - 1 3 9 A Y : 1 ☒ A
17.3 W	940 mm	1230 lm	0 1 1 - 1 3 9 A Z : 1 ☒ A
18.1 W	975 mm	1270 lm	0 1 1 - 1 3 9 B A : 1 ☒ A
18.2 W	1000 mm	1280 lm	0 1 1 - 1 3 0 6 : 1 ☒ A
18.7 W	1010 mm	1320 lm	0 1 1 - 1 3 9 B B : 1 ☒ A
19.4 W	1045 mm	1370 lm	0 1 1 - 1 3 9 B C : 1 ☒ A
20.1 W	1080 mm	1420 lm	0 1 1 - 1 3 9 B D : 1 ☒ A
20.7 W	1115 mm	1460 lm	0 1 1 - 1 3 9 B E : 1 ☒ A
21.4 W	1150 mm	1510 lm	0 1 1 - 1 3 9 B F : 1 ☒ A
21.8 W	1200 mm	1530 lm	0 1 1 - 1 3 0 7 : 1 ☒ A

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour temperature 4000 K, 3500 K. Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions


Order options

WIDTH	W	WIDTH	W	COLOUR TEMPERATURE	W	COLOUR	W
20 mm	1	95 mm	7	3000 K	0	white aluminium RAL 9006	6
35 mm	4	100 mm	8	4000 K	1	tar black RAL 9021	8
50 mm	5			3500 K	2		
85 mm	6						

Planning Information




Electrical mounting accessories (optional)



CONNECTION CABLE

TYPE	ORDER CODE
1 × open / 1 × DC plug	0 1 1 - 9 2 2 2 6 2 0




EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	0 1 1 - 9 2 2 2 1 2 0
2000 mm	0 1 1 - 9 2 2 2 1 4 0
4000 mm	0 1 1 - 9 2 2 2 1 8 0

FLEX CONNECTOR 0-83° electrical

L-W (mm)	ORDER CODE
33-6	0 1 1 - 9 2 2 5 4 0 0




MOUNTING POLE L mechanical / feeder

COLOUR	L-W (mm)	ORDER CODE
white aluminium	180-20	0 1 1 - 9 1 2 1 1 3 6
tar black	180-20	0 1 1 - 9 1 2 1 1 3 8
white aluminium	200-20	0 1 1 - 9 1 2 1 2 3 6
tar black	200-20	0 1 1 - 9 1 2 1 2 3 8
white aluminium	300-20	0 1 1 - 9 1 2 1 3 3 6
tar black	300-20	0 1 1 - 9 1 2 1 3 3 8
white aluminium	180-35	0 1 1 - 9 1 2 4 1 3 6
tar black	180-35	0 1 1 - 9 1 2 4 1 3 8
white aluminium	200-35	0 1 1 - 9 1 2 4 2 3 6

Order options

WIDTH	W	WIDTH	W	COLOUR TEMPERATURE	COLOUR	COLOUR
20 mm	1	95 mm	7	3000 K	0	white aluminium RAL 9006
35 mm	4	100 mm	8	4000 K	1	tar black RAL 9021
50 mm	5			3500 K	2	
85 mm	6					


COLOUR	L-W (mm)	ORDER CODE
tar black	200-35	0 1 1 - 9 1 2 4 2 3 8
white aluminium	300-35	0 1 1 - 9 1 2 4 3 3 6
tar black	300-35	0 1 1 - 9 1 2 4 3 3 8
white aluminium	180-50	0 1 1 - 9 1 2 5 1 3 6
tar black	180-50	0 1 1 - 9 1 2 5 1 3 8
white aluminium	200-50	0 1 1 - 9 1 2 5 2 3 6
tar black	200-50	0 1 1 - 9 1 2 5 2 3 8
white aluminium	300-50	0 1 1 - 9 1 2 5 3 3 6
tar black	300-50	0 1 1 - 9 1 2 5 3 3 8
white aluminium	180-85	0 1 1 - 9 1 2 6 1 3 6
tar black	180-85	0 1 1 - 9 1 2 6 1 3 8
white aluminium	200-85	0 1 1 - 9 1 2 6 2 3 6
tar black	200-85	0 1 1 - 9 1 2 6 2 3 8
white aluminium	300-85	0 1 1 - 9 1 2 6 3 3 6
tar black	300-85	0 1 1 - 9 1 2 6 3 3 8
white aluminium	180-95	0 1 1 - 9 1 2 7 1 3 6
tar black	180-95	0 1 1 - 9 1 2 7 1 3 8
white aluminium	200-95	0 1 1 - 9 1 2 7 2 3 6
tar black	200-95	0 1 1 - 9 1 2 7 2 3 8
white aluminium	300-95	0 1 1 - 9 1 2 7 3 3 6
tar black	300-95	0 1 1 - 9 1 2 7 3 3 8
white aluminium	180-100	0 1 1 - 9 1 2 8 1 3 6
tar black	180-100	0 1 1 - 9 1 2 8 1 3 8
white aluminium	200-100	0 1 1 - 9 1 2 8 2 3 6
tar black	200-100	0 1 1 - 9 1 2 8 2 3 8
white aluminium	300-100	0 1 1 - 9 1 2 8 3 3 6
tar black	300-100	0 1 1 - 9 1 2 8 3 3 8

**MOUNTING POLE T mechanical / electrical**

L-W (mm)	ORDER CODE
180-31	0 1 1 - 9 1 2 2 1 2 ☒
200-31	0 1 1 - 9 1 2 2 2 2 ☒
300-31	0 1 1 - 9 1 2 2 3 2 ☒

**MOUNTING POLE Y mechanical / electrical**

L-W (mm)	ORDER CODE
180-24	0 1 1 - 9 1 2 3 1 2 ☒
200-24	0 1 1 - 9 1 2 3 2 2 ☒
300-24	0 1 1 - 9 1 2 3 3 2 ☒


**MOUNTING POLE Y mechanical / feeder**

L-W (mm)	ORDER CODE
180-24	0 1 1 - 9 1 2 3 1 3 ☒
200-24	0 1 1 - 9 1 2 3 2 3 ☒
300-24	0 1 1 - 9 1 2 3 3 3 ☒

Order options

WIDTH	W	WIDTH	W	COLOUR TEMPERATURE	⚡	COLOUR	☒
20 mm	1	95 mm	7	3000 K	0	white aluminium RAL 9006	6
35 mm	4	100 mm	8	4000 K	1	tar black RAL 9021	8
50 mm	5			3500 K	2		
85 mm	6						

Mounting accessories (optional)



MOUNTING POLE L mechanical

L (mm)	ORDER CODE
180	0 1 1 - 9 1 2 W 1 1 ☒
200	0 1 1 - 9 1 2 W 2 1 ☒
300	0 1 1 - 9 1 2 W 3 1 ☒

Electrical accessories (optional)

POWER SUPPLY 24V EU PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
18 W non DIM	198-264 V AC	η 86 %	130-43-30	0 1 1 - 9 2 1 2 1 1 0
35 W non DIM	198-264 V AC	η 86 %	195-43-30	0 1 1 - 9 2 1 2 2 1 0
100 W non DIM	198-264 V AC	η 92 %	220-43-30	0 1 1 - 9 2 1 2 3 1 0
18 W DALI-2	198-264 V AC	η 84 %	130-43-30	0 1 1 - 9 2 1 2 1 3 0
35 W DALI-2	198-264 V AC	η 89 %	195-43-30	0 1 1 - 9 2 1 2 2 3 0
60 W DALI-2	198-240 V AC	η 93 %	220-43-30	0 1 1 - 9 2 1 2 3 3 0

incl. power cable 2m + connection cable with plug 1m

POWER SUPPLY 24V UL non DIM, 100-305 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
25 W	η 88 %	147-40-32	0 1 1 - 9 2 7 2 1 1 0
40 W	η 88 %	147-40-32	0 1 1 - 9 2 7 2 2 1 0
60 W	η 87 %	176-45-32	0 1 1 - 9 2 7 2 3 1 0

POWER SUPPLY 24V UL incl. metalbox non DIM, 100-305 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
25 W	η 88 %	196-68-45	0 1 1 - 9 2 9 2 1 1 0
40 W	η 88 %	196-68-45	0 1 1 - 9 2 9 2 2 1 0
60 W	η 87 %	223-66-55	0 1 1 - 9 2 9 2 3 1 0

SYSTEM SPLITTER

TYPE	ORDER CODE
3 way	0 1 1 - 9 2 3 8 3 0 0
6 way	0 1 1 - 9 2 3 8 6 0 0

Order options

WIDTH	W	WIDTH	W	COLOUR TEMPERATURE	W	COLOUR	W
20 mm	1	95 mm	7	3000 K	0	white aluminium RAL 9006	6
35 mm	4	100 mm	8	4000 K	1	tar black RAL 9021	8
50 mm	5			3500 K	2		
85 mm	6						

Pole overview



L-SUPPORT standing

EN Arranged linearly along the showcase table, FINA support System, electrically and mechanically connected via the L-Support Poles, ensures excellent illumination of the products or exhibits without restricting the view.

DE Lineare angeordnet entlang des Vitrinen Tisches sorgt FINA support System, elektrisch und mechanisch über die L-Support Pole verbunden, für eine hervorragende Ausleuchtung der Ware oder Exponate, ohne den Blick darauf einzuschränken.



T-SUPPORT standing

EN The T-Support Pole of the FINA support system is primarily used for large display case when several light insets are combined and arranged in a row. The T-Support poles are used to connect them together electrically and mechanically.

DE Die T-Support Pole des FINA support Systems findet vor allem bei großen Vitrinenflächen ihren Einsatz, wenn mehrere Lichteinsätze kombiniert und aneinandergereiht werden. Mittels der T-Support Pole werden diese elektrisch und mechanisch miteinander verbunden.



Y-SUPPORT standing

EN The Y-connectors of the FINA support system enable ideal illumination of the entire display case by allowing different insets to be mechanically and electrically connected to each other, even via corners.

DE Die Y-Connectors des FINA support Systems ermöglichen eine ideale Ausleuchtung der gesamten Vitrine, indem unterschiedliche Insets auch über Ecken miteinander mechanisch und elektrisch verbunden werden können.