

## NOBA

suspended


<sup>EN</sup> Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Apparecchio a sospensione decorativo in alluminio; superficie cromata lucida, alluminio spazzolato o verniciata a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; lente di vetro piano-convesso di qualità; assenza di ombre multiple; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI  $\geq$  90 / 2 SDCM (initial MacAdam)  
 fino a 158 lm/W  
 L80 / 50000 h  
 DALI-2, non DIM  
 IP20

### Types




### Colore



### Cavo



### Distribuzione della luce





free positioning  
by cable and  
hook




high quality  
glass lens

**NOBA 40 suspended****WIDE FLOOD** 69°, CRI ≥ 90



FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.9 W,	2700 K	726 lm	149 lm/W	0 4 9 - 5 3 1 0 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
36 Vf,	3000 K	664 lm	136 lm/W	0 4 9 - 5 3 1 0 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
150 mA	4000 K	695 lm	143 lm/W	0 4 9 - 5 3 1 0 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

**NOBA 50 suspended****WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.8 W,	2700 K	752 lm	155 lm/W	0 4 9 - 5 3 1 3 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
36 Vf,	3000 K	681 lm	141 lm/W	0 4 9 - 5 3 1 3 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
150 mA	4000 K	713 lm	147 lm/W	0 4 9 - 5 3 1 3 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

**NOBA 60 suspended****WIDE FLOOD** 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
4.8 W,	2700 K	765 lm	158 lm/W	0 4 9 - 5 3 1 6 9 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
36 Vf,	3000 K	691 lm	143 lm/W	0 4 9 - 5 3 1 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
150 mA	4000 K	723 lm	150 lm/W	0 4 9 - 5 3 1 6 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W


**Mounting accessories (required)****MOUNTING SET** trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	9-25 mm	75-48	0 0 5 - 3 5 1 1 1 1 7

excl. power supply

**Order options**

COLOUR	COLOUR	COLOUR	CABLE
brushed brass	<input checked="" type="checkbox"/> traffic white RAL 9016	<input checked="" type="checkbox"/> traffic white RAL 9016	<input checked="" type="checkbox"/> white
chrome	4 jet black RAL 9005	8 jet black RAL 9005	8 black
gun metal	5 rose gold	9	
brushed aluminium	6		


**MOUNTING SET with trim for ceilings, 2-25 mm**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	77-49	0 0 5 - 3 5 2 1 1 1 7
jet black	77-49	0 0 5 - 3 5 2 1 1 1 8

excl. power supply

**Mounting accessories (optional)****HOOK surface**

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	16-30	0 3 0 - 1 0 0 0 0 1 7
jet black	16-30	0 3 0 - 1 0 0 0 0 1 8


**Mounting tools accessories (optional)****SPECIAL MOUNTING TOOL for ARY | MOVE IN 45 | NOBA trimless | TULA**

Ø-H (mm)	ORDER CODE
100-107	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless


**Electrical accessories (required)****POWER SUPPLY 150 mA, 198-264 V AC, PC2**

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
6 W   non DIM	η 80 %	93-36-25	0 0 2 - 9 0 8 1 0
15 W   DALI-2	η 87 %	112-29-21	0 0 2 - 9 0 8 1 1

**CANOPY**

CONTROL	Ø-H (mm)	ORDER CODE
non DIM	115-29	0 0 5 - 2 6 0 1 2 1 <a href="#">1</a>
DALI-2	115-29	0 0 5 - 2 6 0 1 2 3 <a href="#">1</a>

incl. power supply

**Electrical accessories (optional)****DIN RAIL POWER SUPPLY BASIC 48 V**

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W   PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime &gt;100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

**DIN RAIL LED DRIVER**

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10-40V SELV

**Order options**

COLOUR	COLOUR	COLOUR	CABLE
brushed brass <input type="checkbox"/>	<input checked="" type="checkbox"/> traffic white RAL 9016	<input type="checkbox"/> traffic white RAL 9016	<input checked="" type="checkbox"/> white
chrome <input type="checkbox"/>	<input type="checkbox"/> jet black RAL 9005	<input checked="" type="checkbox"/> jet black RAL 9005	<input type="checkbox"/> black
gun metal <input type="checkbox"/>	<input type="checkbox"/> rose gold		
brushed aluminium <input type="checkbox"/>			