



SASSO 60 round

wall

^{EN} Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

Plafoniera cilindrica di alluminio da parete; inserto verniciato; superficie housing verniciata a polv.; a scelta emissione simmetrica diretta oppure diretta/indiretta; distribuzione equilibrata per una luminosità omogenea del soffitto o parete; emissione precisa con ottica lenticolare di alta qualità; montaggio della variante DIRECT per illuminare il pavimento oppure il soffitto; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 fino a ↓ 713 lm / ↑ 712 lm
 fino a 70 lm/W
 L80 / 50000 h
 DALI-2, non DIM
 IP20

Types



Colore



Colore interno



Distribuzione della luce



direct and
 direct / indirect
 illumination



high quality lens



easy mounting



CRI ≥ 95 2
 SDCM
 (optional)




SASSO 60 round direct wall



OPAL LENS | DIRECT 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.3 W	2700 K	661 lm	64 lm/W	0 4 8 - 3 1 5 0 4 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	686 lm	67 lm/W	0 4 8 - 3 1 5 0 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	716 lm	70 lm/W	0 4 8 - 3 1 5 0 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.




SASSO 60 round direct / indirect wall



OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.6 W	2700 K	↓659/↑657 lm	64 lm/W	0 4 8 - 3 1 6 0 4 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	↓683/↑682 lm	66 lm/W	0 4 8 - 3 1 6 0 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓713/↑712 lm	69 lm/W	0 4 8 - 3 1 6 0 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9