

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 22, UGR ≤ 25
fino a ↓ 713 lm / ↑ 712 lm
fino a 70 lm/W
L90 / 100000 h
DALI-2, non DIM
IP20

Types



Colours

Colore interno

Distribuzione della luce

SASSO 60 round

wall

EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

IT Plafoniera cilindrica di alluminio da parete; inserto verniciato; superficie housing verniciata a polv.; a scelta emissione simmetrica diretta oppure diretta/indiretta; distribuzione equilibrata per una luminosità omogenea del soffitto o parete; emissione precisa con ottica lenticolare di alta qualità; montaggio della variante DIRECT per illuminare il pavimento oppure il soffitto; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica



direct and direct / indirect illumination



high quality lens



easy mounting



CRI ≥ 95 2 SDCM (optional)





SASSO 60 round direct wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.3 W	2700 K	661 lm	64 lm/W	0 4 8 - 3 1 5 0 4 ◪ ■ O
	3000 K	686 lm	67 lm/W	0 4 8 - 3 1 5 0 5 ◪ ■ O
	4000 K	716 lm	70 lm/W	0 4 8 - 3 1 5 0 6 ◪ ■ O

The data values for the luminous flux of fraction may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.





SASSO 60 round direct / indirect wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.6 W	2700 K	↧659/↥657 lm	64 lm/W	0 4 8 - 3 1 6 0 4 ◪ ■ O
	3000 K	↧683/↥682 lm	66 lm/W	0 4 8 - 3 1 6 0 5 ◪ ■ O
	4000 K	↧713/↥712 lm	69 lm/W	0 4 8 - 3 1 6 0 6 ◪ ■ O

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9