


Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 22, UGR ≤ 25
fino a ↓ 1.200 lm / ↑ 1.200 lm
fino a 69 lm/W
L90 / 100000 h
DALI-2, non DIM
IP20

Types



Colours



Colore interno



Distribuzione della luce



SASSO 100 round

wall

EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

IT Plafoniera cilindrica di alluminio da parete; inserto verniciato; superficie housing verniciata a polv.; a scelta emissione simmetrica diretta oppure diretta/indiretta; distribuzione equilibrata per una luminosità omogenea del soffitto o parete; emissione precisa con ottica lenticolare di alta qualità; montaggio della variante DIRECT per illuminare il pavimento oppure il soffitto; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica



direct and direct / indirect illumination



high quality lens




easy mounting



CRI ≥ 95 2 SDCM (optional)






SASSO 100 round direct wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.9 W	2700 K	1110 lm	62 lm/W	048 - 34509 ◆ ◪ ■ O
	3000 K	1150 lm	64 lm/W	048 - 34500 ◆ ◪ ■ O
	3500 K	1170 lm	65 lm/W	048 - 34502 ◆ ◪ ■ O
	4000 K	1200 lm	67 lm/W	048 - 34501 ◆ ◪ ■ O



SASSO 100 round direct / indirect wall

CRI ≥ 90 | 2 SDCM | 220-240 V | 1 ADDR. | X-PERT | X-PERT

OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
35.0 W	2700 K	↧1110/↥1110 lm	63 lm/W	048 - 34609 ◆ ◪ ■ O
	3000 K	↧1150/↥1150 lm	66 lm/W	048 - 34600 ◆ ◪ ■ O
	↧ 3500 K/ ↥3000 K	↧1170/↥1170 lm	67 lm/W	048 - 34602 ◆ ◪ ■ O
	↧ 4000 K/ ↥4000K	↧1200/↥1200 lm	69 lm/W	048 - 34601 ◆ ◪ ■ O



Optical accessories

HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø·H (mm)	ORDER CODE
jet black	50·3	007 - 1965598

Order options

CONTROL ◆		COLOUR ◪		INNER COLOUR ■	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9

MAM Competence Center, Großhöflein

Austria

Architetto
INNOCAD Architektur
ZT

Lighting Design
INNOCAD Architektur
ZT

Fotografo
Paul Ott



Prodotti utilizzati



TASK round suspended



LITO 60 suspended



SONIC free standing



SASSO 100 round suspended



SASSO 100 round wall

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



