

Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM
(initial MacAdam)
UGR ≤ 16, UGR ≤ 19
fino a 177 lm/W
L90 / 100000 h
DALI-2
IP20

Types



Colours

Inserto

Distribuzione della luce



suitable for grid ceilings



easy mounting



up to 177 lm/W (high efficiency)



DIN EN 12464-1 UGR ≤ 19

INTO

recessed

EN Square or rectangular lay-in luminaire made of sheet steel; optionally for modular ceilings 600 x 600 or 625 x 625 with visible grid system; surface powder coated; optionally two or three linear light insets made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminium-vaporised surface; or with specially computed wide beam lenses; precise radiation characteristic with symmetrical light distribution; exchangeable light insets; incl. converter, suitable for through-wiring; plug and play connection cables between light insets and converter with plug/socket system; energy-efficient LEDs with very good colour rendering

IT Apparecchio quadrato o rettangolare da incasso in lamiera d'acciaio; a scelta per controsoffitti modulari 600 x 600 o 625 x 625 con sistema di supporto a griglia visibile; verniciatura a polvere; a scelta due o tre inserti luminosi lineari in plastica; dotato di singoli punti luce a LED; ottima schermatura con superficie di emissione arretrata; comunque maggiore efficienza con la speciale tecnologia delle lenti; lenti con emissione wide flood; o riflettore di alta qualità con superficie a microfaccette e vaporizzata in alluminio; o dotati di lenti wide beam appositamente tarate; caratteristica di emissione precisa con distribuzione simmetrica della luce; inserti luminosi intercambiabili; incl. convertitore, adatto per il cablaggio passante; cavi di collegamento preassemblati tra gli inserti luminosi e il convertitore con sistema a spina/presa; LED ad efficienza energetica con elevata resa cromatica





INTO 600 2 reflectors recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SUPER WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
20.0 W	3000 K	80	3250 lm	163 lm/W	064-510053 7 ■ X
		90	2830 lm	142 lm/W	064-510003 7 ■ X
	4000 K	80	3460 lm	173 lm/W	064-510063 7 ■ X
		90	2830 lm	142 lm/W	064-510013 7 ■ X
24.5 W	tunable w.	90	3250 lm	133 lm/W	064-5100D3 7 ■ X





INTO 600 3 reflectors recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SUPER WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
29.3 W	3000 K	80	4870 lm	166 lm/W	064-510153 7 ■ X
		90	4240 lm	145 lm/W	064-510103 7 ■ X
	4000 K	80	5190 lm	177 lm/W	064-510163 7 ■ X
		90	4240 lm	145 lm/W	064-510113 7 ■ X
36.0 W	tunable w.	90	4870 lm	135 lm/W	064-5101D3 7 ■ X





INTO 625 2 reflectors recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SUPER WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
20.0 W	3000 K	80	3250 lm	163 lm/W	064-511053 7 ■ X
		90	2830 lm	142 lm/W	064-511003 7 ■ X
	4000 K	80	3460 lm	173 lm/W	064-511063 7 ■ X
		90	2830 lm	142 lm/W	064-511013 7 ■ X
24.5 W	tunable w.	90	3250 lm	133 lm/W	064-5110D3 7 ■ X

Order options

INSET	■
black	B
chrome	R





INTO 625 3 reflectors recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SUPER WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
29.3 W	3000 K	80	4870 lm	166 lm/W	0 6 4 - 5 1 1 1 5 3 7 ■ X
		90	4240 lm	145 lm/W	0 6 4 - 5 1 1 1 0 3 7 ■ X
	4000 K	80	5190 lm	177 lm/W	0 6 4 - 5 1 1 1 6 3 7 ■ X
		90	4240 lm	145 lm/W	0 6 4 - 5 1 1 1 1 3 7 ■ X
36.0 W	tunable w.	90	4870 lm	135 lm/W	0 6 4 - 5 1 1 1 D 3 7 ■ X





INTO 1250 reflector recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SUPER WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
39.0 W	3000 K	80	6500 lm	167 lm/W	0 6 4 - 5 1 2 0 5 3 7 ■ X
		90	5660 lm	145 lm/W	0 6 4 - 5 1 2 0 0 3 7 ■ X
	4000 K	80	6920 lm	177 lm/W	0 6 4 - 5 1 2 0 6 3 7 ■ X
		90	5660 lm	145 lm/W	0 6 4 - 5 1 2 0 1 3 7 ■ X
48.0 W	tunable w.	90	6500 lm	135 lm/W	0 6 4 - 5 1 2 0 D 3 7 ■ X





INTO 600 2 spotlines recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
24.5 W	tunable w.	90	3110 lm	127 lm/W	0 6 4 - 5 2 0 0 D 3 7 ■$_1$ W
25.1 W	3000 K	80	3920 lm	156 lm/W	0 6 4 - 5 2 0 0 5 3 7 ■$_1$ W
		90	3410 lm	136 lm/W	0 6 4 - 5 2 0 0 0 3 7 ■$_1$ W
	4000 K	80	4170 lm	166 lm/W	0 6 4 - 5 2 0 0 6 3 7 ■$_1$ W
		90	3410 lm	136 lm/W	0 6 4 - 5 2 0 0 1 3 7 ■$_1$ W

Order options

INSET ■	
black	B
chrome	R

INSET ■$_1$	
chrome	4
traffic white RAL 9016	7
jet black RAL 9005	8
gold	9





INTO 600 3 spotlines recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
36.0 W	tunable w.	90	4670 lm	130 lm/W	064-5201D37 ■ W
37.0 W	3000 K	80	5880 lm	159 lm/W	064-5201537 ■ W
		90	5120 lm	138 lm/W	064-5201037 ■ W
	4000 K	80	6260 lm	169 lm/W	064-5201637 ■ W
		90	5120 lm	138 lm/W	064-5201137 ■ W





INTO 625 2 spotlines recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
24.5 W	tunable w.	90	3110 lm	127 lm/W	064-5210D37 ■ W
25.1 W	3000 K	80	3920 lm	156 lm/W	064-5210537 ■ W
		90	3410 lm	136 lm/W	064-5210037 ■ W
	4000 K	80	4170 lm	166 lm/W	064-5210637 ■ W
		90	3410 lm	136 lm/W	064-5210137 ■ W





INTO 625 3 spotlines recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
36.0 W	tunable w.	90	4670 lm	130 lm/W	064-5211D37 ■ W
37.0 W	3000 K	80	5880 lm	159 lm/W	064-5211537 ■ W
		90	5120 lm	138 lm/W	064-5211037 ■ W
	4000 K	80	6260 lm	169 lm/W	064-5211637 ■ W
		90	5120 lm	138 lm/W	064-5211137 ■ W

Order options

INSET	■
chrome	4
traffic white RAL 9016	7
jet black RAL 9005	8
gold	9





INTO 1250 spotline recessed

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
47.0 W	3000 K	80	7480 lm	159 lm/W	0 6 4 - 5 2 2 0 5 3 7 ■1 W
		90	6510 lm	139 lm/W	0 6 4 - 5 2 2 0 0 3 7 ■1 W
	4000 K	80	7960 lm	169 lm/W	0 6 4 - 5 2 2 0 6 3 7 ■1 W
		90	6510 lm	139 lm/W	0 6 4 - 5 2 2 0 1 3 7 ■1 W
48.0 W	tunable w.	90	6220 lm	130 lm/W	0 6 4 - 5 2 2 0 D 3 7 ■1 W





INTO 600 2 lenses recessed

CRI ≥ 90 | UGR ≤ 19 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
25.9 W	3000 K	80	4210 lm	163 lm/W	0 6 4 - 5 3 0 0 5 3 7 0 W
		90	3670 lm	142 lm/W	0 6 4 - 5 3 0 0 0 3 7 0 W
	4000 K	80	4480 lm	173 lm/W	0 6 4 - 5 3 0 0 6 3 7 0 W
		90	3670 lm	142 lm/W	0 6 4 - 5 3 0 0 1 3 7 0 W





INTO 600 3 lenses recessed

CRI ≥ 90 | UGR ≤ 19 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
38.0 W	3000 K	80	6320 lm	166 lm/W	0 6 4 - 5 3 0 1 5 3 7 0 W
		90	5500 lm	145 lm/W	0 6 4 - 5 3 0 1 0 3 7 0 W
	4000 K	80	6720 lm	177 lm/W	0 6 4 - 5 3 0 1 6 3 7 0 W
		90	5500 lm	145 lm/W	0 6 4 - 5 3 0 1 1 3 7 0 W

Order options

INSET	■1
chrome	4
traffic white RAL 9016	7
jet black RAL 9005	8
gold	9



INTO 625 2 lenses recessed

CRI ≥ 90 · UGR ≤ 19 · 220-240 V · 1 ADDR. · X-PERT · X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
25.9 W	3000 K	80	4210 lm	163 lm/W	064-531053700W
		90	3670 lm	142 lm/W	064-531003700W
	4000 K	80	4480 lm	173 lm/W	064-531063700W
		90	3670 lm	142 lm/W	064-531013700W





INTO 625 3 lenses recessed

CRI ≥ 90 · UGR ≤ 19 · 220-240 V · 1 ADDR. · X-PERT · X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
38.0 W	3000 K	80	6320 lm	166 lm/W	064-531153700W
		90	5500 lm	145 lm/W	064-531103700W
	4000 K	80	6720 lm	177 lm/W	064-531163700W
		90	5500 lm	145 lm/W	064-531113700W





INTO 1250 lens recessed

CRI ≥ 90 · UGR ≤ 19 · 220-240 V · 1 ADDR. · X-PERT · X-PERT

WIDE FLOOD traffic white, DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
49.0 W	3000 K	80	8140 lm	166 lm/W	064-532053700W
		90	7090 lm	145 lm/W	064-532003700W
	4000 K	80	8660 lm	177 lm/W	064-532063700W
		90	7090 lm	145 lm/W	064-532013700W

