






Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 19
fino a 139 lm/W
L90 / 100000 h, L90 / 50000 h
DALI-2
Opal, Reflector
IP20

Types



Colours



Riflettore



Distribuzione della luce



MITA circle 200

recessed

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; high gloss reflector with faceted design; opal cover for uniform illumination; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante circolare in alluminio pressofuso; forma estremamente sottile; apparecchio da incasso con bordo perimetrale; per soffitti di spessore 2-25 mm; verniciatura a polvere; riflettore ad alta lucentezza con design sfaccettato; diffusore opale per un'illuminazione omogenea; LED ad efficienza energetica con elevata resa cromatica




suitable for plasterboard or grid ceilings



DIN EN 12464-1
UGR ≤ 19




tunable white
2700 – 6500 K



MITA CIRCLE 200 opal trim

TUNABLE WHITE | CRI ≥ 90 | 220-240 V | 1 ADDR. | X-PERT | X-PERT




OPAL DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.2 W	3000 K, CRI ≥ 90	1670 lm	97 lm/W	0 7 4 - 8 1 2 3 0 3 ◪ O
	4000 K, CRI ≥ 90	1670 lm	97 lm/W	0 7 4 - 8 1 2 3 1 3 ◪ O
17.5 W	3000 K, CRI ≥ 80	1760 lm	101 lm/W	0 7 4 - 8 1 2 3 5 3 ◪ O
	4000 K, CRI ≥ 80	1830 lm	105 lm/W	0 7 4 - 8 1 2 3 6 3 ◪ O
21.6 W	tunable w., CRI ≥ 90	1820 lm	84 lm/W	0 7 4 - 8 1 2 3 D 3 ◪ O



MITA CIRCLE 200 reflector trim

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT



REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
13.2 W	3000 K, CRI ≥ 90	chrome	1700 lm	129 lm/W	0 7 4 - 8 1 2 3 0 3 ◪ R
		dark chr.	1220 lm	92 lm/W	0 7 4 - 8 1 2 3 0 3 ◪ B
	4000 K, CRI ≥ 90	chrome	1700 lm	129 lm/W	0 7 4 - 8 1 2 3 1 3 ◪ R
		dark chr.	1220 lm	92 lm/W	0 7 4 - 8 1 2 3 1 3 ◪ B
13.5 W	3000 K, CRI ≥ 80	chrome	1800 lm	133 lm/W	0 7 4 - 8 1 2 3 5 3 ◪ R
		dark chr.	1290 lm	96 lm/W	0 7 4 - 8 1 2 3 5 3 ◪ B
	4000 K, CRI ≥ 80	chrome	1870 lm	139 lm/W	0 7 4 - 8 1 2 3 6 3 ◪ R
		dark chr.	1340 lm	99 lm/W	0 7 4 - 8 1 2 3 6 3 ◪ B
15.6 W	tunable w., CRI ≥ 90	chrome	1750 lm	112 lm/W	0 7 4 - 8 1 2 3 D 3 ◪ R
		dark chr.	1250 lm	80 lm/W	0 7 4 - 8 1 2 3 D 3 ◪ B

Order options

COLOUR	◪
traffic white RAL 9016	7
jet black RAL 9005	8