



Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
fino a 153 lm/W
L80 / 50000 h
IP20

Types





Colours



Cavo



Distribuzione della luce




NOBA

multi suspended

EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; round ceiling surface mounted canopy (black or white) optionally for two to five lamps or two to ten lamps fittings; or linear ceiling surface mounted canopy (black or white) optionally for two to five lamps fittings; high quality plano-convex glass lens; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

IT Apparecchio a sospensione decorativo in alluminio; superficie cromata lucida, alluminio spazzolato o verniciata a polvere; sospeso con cavo a sospensione, incl. cavo di alimentazione (nero o bianco); accorciabile a piacere; rosone rotondo per montaggio a soffitto (nero o bianco) a scelta per apparecchi da due a cinque luci o da due a dieci luci; o rosone lineare per montaggio a soffitto (nero o bianco) a scelta per apparecchi da due a cinque luci; lente di vetro piano-convesso di qualità; LED ad efficienza energetica con elevata resa cromatica; rosone per cablaggio passante; convertitore integrato nel rosone; anelli di montaggio a soffitto per posizionare la lampada in più punti dell'ambiente disponibili come accessori



free positioning by cable and hook



high quality glass lens




NOBA 40 multi suspended

CRI ≥ 90 · 2 SDCM · UGR ≤ 22 · cd/m² ≤ 1500 · III · X-PERT

WIDE FLOOD 69°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	326 lm	133 lm/W	0 4 9 - 5 4 1 0 9 1 ◪ ■ W
9 Vf,	3000 K	322 lm	135 lm/W	0 4 9 - 5 4 1 0 0 1 ◪ ■ W
300 mA	4000 K	352 lm	144 lm/W	0 4 9 - 5 4 1 0 1 1 ◪ ■ W






NOBA 50 multi suspended

CRI ≥ 90 · 2 SDCM · UGR ≤ 19 · cd/m² ≤ 1500 · III · X-PERT

WIDE FLOOD 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.4 W,	2700 K	345 lm	141 lm/W	0 4 9 - 5 4 1 3 9 1 ◪ ■ W
9 Vf,	3000 K	342 lm	143 lm/W	0 4 9 - 5 4 1 3 0 1 ◪ ■ W
300 mA	4000 K	374 lm	153 lm/W	0 4 9 - 5 4 1 3 1 1 ◪ ■ W






NOBA 60 multi suspended

CRI ≥ 90 · 2 SDCM · UGR ≤ 16 · cd/m² ≤ 1500 · III · X-PERT

WIDE FLOOD 67°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2.5 W,	2700 K	325 lm	132 lm/W	0 4 9 - 5 4 1 6 9 1 ◪ ■ W
9 Vf,	3000 K	337 lm	137 lm/W	0 4 9 - 5 4 1 6 0 1 ◪ ■ W
300 mA	4000 K	352 lm	143 lm/W	0 4 9 - 5 4 1 6 1 1 ◪ ■ W



Mounting accessories (optional)




HOOK surface

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	16·30	0 3 0 - 1 0 0 0 0 1 7
jet black	16·30	0 3 0 - 1 0 0 0 0 1 8

Order options

COLOUR ◪		COLOUR ◪		CABLE ■	
brushed brass	3	traffic white RAL 9016	7	white	7
chrome	4	jet black RAL 9005	8	black	8
gun metal	5	rose gold	9		
brushed aluminium	6				


Electrical accessories (required)



CANOPY WITH SLOTS multi round 2-10 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 0 1 3
Casambi	380·43	0 0 5 - 2 6 9 0 1 9


2 converter a 300 mA; 2 DALI addresses



CANOPY WITH SLOTS multi round 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 0 0 3
Casambi	380·43	0 0 5 - 2 6 9 0 0 9


1 DALI address



CANOPY WITHOUT SLOTS multi round 2-10 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 1 1 3
Casambi	380·43	0 0 5 - 2 6 9 1 1 9


2 converter a 300 mA; 2 DALI addresses



CANOPY WITHOUT SLOTS multi round 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	Ø·H (mm)	ORDER CODE
DALI-2	380·43	0 0 5 - 2 6 9 1 0 3
Casambi	380·43	0 0 5 - 2 6 9 1 0 9

1 DALI address



CANOPY multi linear 2-5 insets 220-240 V AC, 50-60 Hz, PC 1

CONTROL	L·W·H (mm)	ORDER CODE
DALI-2	1000·34·50	0 0 5 - 2 6 9 2 0 3
Casambi	1000·34·50	0 0 5 - 2 6 9 2 0 9

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8