



SASSO 60 round adjustable

recessed 1 lamp

^{EN} Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; light inset rotatable and tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

^{IT} Faretto a incasso rotondo; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura; incasso possibile in vari telai; inserto luce girevole e orientabile; emissione precisa con ottica lenticolare di alta qualità; tecnologia COB (Chip on Board) per la massima efficienza (ADJUSTABLE e DOWNLIGHT); assenza di ombre multiple; LED efficienti con alta resa cromatica

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
colour warm dimming 1800 - 3000
K
CRI \geq 90 / 2 SDCM (initial MacAd,
3 SDCM (initial MacAd
UGR \leq 13, UGR \leq 16, UGR \leq 19
fino a 107 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
front IP40, back IP20

Types




Colore



Set di montaggio



Distribuzione della luce



rotatable 360°,
tiltable 30°



glare control
(UGR \leq 16)



60 mm
recessed depth



Colour Warm
Dimming 1800 -
3000 K



SASSO 60 round adjustable



SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.9 W, 36 Vf, 300 mA	2700 K	879 lm	81 lm/W	0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> S
	3000 K	908 lm	84 lm/W	0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> S
	3500 K	927 lm	85 lm/W	0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> S
	4000 K	956 lm	88 lm/W	0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> S

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.



MEDIUM 26°-27°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	781 lm	76 lm/W	0 4 8 - 2 6 2 2 E 1 <input checked="" type="checkbox"/> M
10.6 W, 36 Vf, 300 mA	2700 K	1040 lm	98 lm/W	0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> M
	3000 K	1080 lm	102 lm/W	0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> M
	3500 K	1110 lm	104 lm/W	0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> M
	4000 K	1130 lm	106 lm/W	0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> M

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver

FLOOD 36°-41°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W, 300 mA	CWD	745 lm	73 lm/W	0 4 8 - 2 6 2 2 E 1 <input checked="" type="checkbox"/> F
10.6 W, 36 Vf, 300 mA	2700 K	992 lm	93 lm/W	0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> F
	3000 K	1030 lm	97 lm/W	0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> F
	3500 K	1050 lm	99 lm/W	0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> F
	4000 K	1070 lm	101 lm/W	0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> F

The data values for the luminaire luminous flux may differ for specific order options by -14%. Luminous flux value refers to colour matt silver, traffic white. CWD only for DALI-2; not for DIN-RAIL LED Driver


WIDE FLOOD 56°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.6 W, 36 Vf, 300 mA	2700 K	1050 lm	98 lm/W	0 4 8 - 2 6 2 2 9 1 <input checked="" type="checkbox"/> W
	3000 K	1090 lm	102 lm/W	0 4 8 - 2 6 2 2 0 1 <input checked="" type="checkbox"/> W
	3500 K	1110 lm	104 lm/W	0 4 8 - 2 6 2 2 2 1 <input checked="" type="checkbox"/> W
	4000 K	1130 lm	107 lm/W	0 4 8 - 2 6 2 2 1 1 <input checked="" type="checkbox"/> W

The data values for the luminaire luminous flux may differ for specific order options by -11%. Luminous flux value refers to colour matt silver, traffic white.

Electrical mounting accessories (optional)

THROUGH WIRING CONNECTION BOX




TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
matt silver	4		
traffic white RAL 9016	7		
gold dust RAL 260-M	9		


**MOUNTING SET trimless** for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	73-29	0 4 8 - 2 6 9 6 1 1 7



for SASSO 60 round | SPIO 60 downlight

**MOUNTING SET trimless** for soft acoustic ceilings


COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
traffic white	25-40 mm	80-25	0 4 8 - 2 6 9 6 1 9 7

**MOUNTING SET with trim 25-40 mm**, for soft acoustic ceilings


COLOUR	Ø-H (mm)	ORDER CODE
traffic white	80-27	0 4 8 - 2 6 9 6 3 9 7
jet black	80-27	0 4 8 - 2 6 9 6 3 9 8

**MOUNTING SET with trim 1 lamp 2-25 mm**, for intermediate ceilings

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	80-40	0 4 8 - 2 6 9 6 3 1 7
jet black	80-40	0 4 8 - 2 6 9 6 3 1 8
white aluminium	80-40	0 4 8 - 2 6 9 6 3 1 G

Mounting accessories (optional)**EXPOSED CONCRETE MOUNTING HOUSING**

COLOUR	L-W-H (mm)	ORDER CODE
white aluminium	230-230-162	0 4 8 - 2 6 9 5 2 1 0

**PRIMED CONCRETE MOUNTING HOUSING**

L-W-H (mm)	ORDER CODE
614-307-120	0 4 8 - 2 6 9 5 1 1 0

order mounting set separately

Mounting tools accessories (optional)**MOUNTING TOOL** for soft acoustic ceilings

COLOUR	L-W-H (mm)	ORDER CODE
traffic black	77-77-35	0 4 8 - 2 6 9 5 9 1 8

Electrical accessories (required)**POWER SUPPLY PC2**, 198-264 V AC, 300 mA

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
13 W non DIM	η 87 %	85-40-22	0 0 2 - 9 0 7 7 1
15 W DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 9 0

Electrical accessories (optional)**DIN RAIL LED DRIVER**

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

Order options

COLOUR	
jet black RAL 9005	<input checked="" type="checkbox"/> 1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

200 -1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V

DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime @ 120W, 45° ambient temp., cascadable max. 3 devices

POWER SUPPLY PRE-WIRED with junction box PC2, 198-264 V AC

TYPE	EFFICIENCY	ORDER CODE
300 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A
250 mA 15 W DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA 15 W non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
250 mA 10 W non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A

POWER SUPPLY with loop through function PC2, 15 W, 198-264 V AC, DALI-2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
300 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 7 0
250 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 4 7

Order options**COLOUR**

jet black RAL 9005	<input checked="" type="checkbox"/>	1
matt silver	<input type="checkbox"/>	4
traffic white RAL 9016	<input type="checkbox"/>	7
gold dust RAL 260-M	<input type="checkbox"/>	9