



MINO 25

recessed


^{EN} Luminaire housing from extruded aluminium profile, angular design; recessed luminaire with trim; surface raw or powder coated; high quality reflector with micro-faceted, aluminum-vaporised surface; or fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; precise radiation characteristic with symmetrical light distribution; or completely homogeneously illuminated, opal cover; converter integrated into luminaire housing; energy-efficient LEDs with very good colour rendering

^{IT} Corpo illuminante in profilo di alluminio estruso, modello squadrato; apparecchio da incasso con bordo perimetrale; finitura grezza o verniciata a polvere; riflettore di alta qualità con superficie a microfacette e vaporizzata in alluminio; o dotato di singoli punti luce a LED; ottima schermatura con superficie di emissione arretrata; comunque maggiore efficienza con la speciale tecnologia delle lenti; lenti con emissione wide flood; caratteristica di emissione precisa con distribuzione simmetrica della luce; o illuminazione completamente omogenea, cover opalina; convertitore integrato nel corpo illuminante; LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM
 (initial MacAdam)
 UGR ≤ 16, UGR ≤ 19
 fino a 168 lm/W
 L90 / 100000 h, L90 / 50000 h
 DALI-2
 Wideflood
 IP20

Types



Colore



Inserto




Distribuzione della luce




black & chrome
louver



up to 168 lm/W
(high efficiency)




MINO 25 louver trim





LOUVER DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1730 lm	162 lm/W	0 4 3 - 0 0 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		90	1420 lm	133 lm/W	0 4 3 - 0 0 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
20.6 W	2004 mm	80	3470 lm	168 lm/W	0 4 3 - 0 0 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		90	2840 lm	138 lm/W	0 4 3 - 0 0 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
27.5 W	2754 mm	80	4630 lm	168 lm/W	0 4 3 - 0 0 0 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		90	3790 lm	138 lm/W	0 4 3 - 0 0 0 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour temperature 4000 K.



MINO 25 spotline trim



SPOTLINE DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1710 lm	160 lm/W	0 4 3 - 0 0 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		90	1400 lm	131 lm/W	0 4 3 - 0 0 1 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
20.6 W	2004 mm	80	3410 lm	166 lm/W	0 4 3 - 0 0 1 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		90	2790 lm	135 lm/W	0 4 3 - 0 0 1 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
27.5 W	2754 mm	80	4560 lm	166 lm/W	0 4 3 - 0 0 1 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		90	3730 lm	136 lm/W	0 4 3 - 0 0 1 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inset traffic white colour temperature 4000 K.

Order options

COLOUR TEMPERATURE	☼	COLOUR TEMPERATURE	☼	COLOUR	☑	INSET	■
3000 K	0	3000 K	5	aluminium raw	0	chrome reflector	4
4000 K	1	4000 K	6	signal white RAL 9003	7	black reflector	8
				signal black RAL 9004	8		

INSET	■
traffic white RAL 9016	7
jet black RAL 9005	8