


Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM
(initial MacAdam)
UGR ≤ 16, UGR ≤ 19
fino a 176 lm/W
L90 / 100000 h
DALI-2
IP20

Types





Colours



Inserto



Distribuzione della luce



ENVIVA

track

EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; suitable for mounting in 3-phase power tracks; converter in the adapter; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with symmetrical light distribution; efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks

IT Corpo illuminante in profilo di alluminio estruso, modello squadrato; forma estremamente sottile (solo 45 x 15 mm); nessuna vite visibile; finitura grezza o verniciata a polvere; adatto per il montaggio su binari elettrificati trifase; convertitore nell'adattatore; inserto luminoso lineare in plastica; dotato di singoli punti luce a LED; ottima schermatura con superficie di emissione arretrata; comunque maggiore efficienza con la speciale tecnologia delle lenti; lenti con emissione wide flood; o riflettore di alta qualità con superficie a microfaccette e vaporizzata in alluminio; caratteristica di emissione precisa con distribuzione simmetrica della luce; LED efficienti con alta resa cromatica; adattatore per installazione senza utensili o scorrimento in vari binari trifase



DIN EN 12464-1
UGR ≤ 16



up to 176 lm/W
(high efficiency)




ENVIVA lens track

CRI ≥90 | UGR ≤19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

LENS DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.6 W	1204 mm	3000 K	80	3240 lm	165 lm/W	067-263453◪W
			90	2820 lm	144 lm/W	067-263403◪W
		4000 K	80	3450 lm	176 lm/W	067-263463◪W
			90	2820 lm	144 lm/W	067-263413◪W
24.8 W	1504 mm	3000 K	80	4100 lm	165 lm/W	067-263553◪W
			90	3570 lm	144 lm/W	067-263503◪W
		4000 K	80	4370 lm	176 lm/W	067-263563◪W
			90	3570 lm	144 lm/W	067-263513◪W






ENVIVA louver track

CRI ≥90 | UGR ≤19 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

LOUVER DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1204 mm	3000 K	80	3260 lm	165 lm/W	067-063453◪■X
			90	2840 lm	144 lm/W	067-063403◪■X
		4000 K	80	3470 lm	176 lm/W	067-063463◪■X
			90	2840 lm	144 lm/W	067-063413◪■X
25.1 W	1504 mm	3000 K	80	4120 lm	164 lm/W	067-063553◪■X
			90	3590 lm	143 lm/W	067-063503◪■X
		4000 K	80	4380 lm	175 lm/W	067-063563◪■X
			90	3590 lm	143 lm/W	067-063513◪■X






ENVIVA spotline track

CRI ≥90 | UGR ≤16 | cd/m² ≤1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SPOTLINE DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1204 mm	3000 K	80	3180 lm	161 lm/W	067-163453◪■$_1$W
			90	2770 lm	141 lm/W	067-163403◪■$_1$W
		4000 K	80	3390 lm	172 lm/W	067-163463◪■$_1$W
			90	2770 lm	141 lm/W	067-163413◪■$_1$W
25.1 W	1504 mm	3000 K	80	4020 lm	160 lm/W	067-163553◪■$_1$W
			90	3500 lm	139 lm/W	067-163503◪■$_1$W
		4000 K	80	4280 lm	171 lm/W	067-163563◪■$_1$W
			90	3500 lm	139 lm/W	067-163513◪■$_1$W



Order options

COLOUR ◪		INSET ■		INSET ■$_1$	
aluminium raw	0	chrome reflector	4	traffic white RAL 9016	7
traffic white RAL 9016	7	black reflector	8	jet black RAL 9005	8
jet black RAL 9005	8				