




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 16, UGR ≤ 19, UGR ≤ 22
fino a 144 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
front IP40, back IP20

Types



Colours



Set di montaggio



Distribuzione della luce



SASSO 100 square high efficient adjustable

recessed 1 lamp

EN Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; light inset tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

IT Faretto a incasso quadrato; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili (con o senza bordo perimetrale); verniciatura; incasso possibile in vari telai; inserto luce orientabile; emissione precisa con ottica lenticolare di alta qualità; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica




glare control (UGR ≤ 16)



60 mm recessed depth



SASSO 100 square high efficient adjustable



SPOT 20°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.5 W, 36 Vf, 450 mA	2700 K	2060 lm	133 lm/W	048-273391 S
	3000 K	2140 lm	138 lm/W	048-273301 S
	3500 K	2170 lm	140 lm/W	048-273321 S
	4000 K	2180 lm	140 lm/W	048-273311 S
23.2 W, 36 Vf, 650 mA	2700 K	2740 lm	118 lm/W	048-273391 S
	3000 K	2850 lm	123 lm/W	048-273301 S
	3500 K	2890 lm	125 lm/W	048-273321 S
	4000 K	2890 lm	125 lm/W	048-273311 S

The data values for the luminous flux of fraction may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

MEDIUM 31°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.5 W, 36 Vf, 450 mA	2700 K	2070 lm	133 lm/W	048-273391 M
	3000 K	2150 lm	139 lm/W	048-273301 M
	3500 K	2180 lm	140 lm/W	048-273321 M
	4000 K	2180 lm	141 lm/W	048-273311 M
23.2 W, 36 Vf, 650 mA	2700 K	2750 lm	119 lm/W	048-273391 M
	3000 K	2860 lm	124 lm/W	048-273301 M
	3500 K	2900 lm	125 lm/W	048-273321 M
	4000 K	2910 lm	125 lm/W	048-273311 M

FLOOD 39°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.5 W, 36 Vf, 450 mA	2700 K	1970 lm	127 lm/W	048-273391 F
	3000 K	2050 lm	132 lm/W	048-273301 F
	3500 K	2080 lm	134 lm/W	048-273321 F
	4000 K	2080 lm	134 lm/W	048-273311 F
23.2 W, 36 Vf, 650 mA	2700 K	2620 lm	113 lm/W	048-273391 F
	3000 K	2730 lm	118 lm/W	048-273301 F
	3500 K	2760 lm	119 lm/W	048-273321 F
	4000 K	2770 lm	119 lm/W	048-273311 F

The data values for the luminous flux of fraction may differ for specific order options by -9%. Luminous flux value refers to colour traffic white.


Order options

COLOUR	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

WIDE FLOOD 56°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.5 W, 36 Vf, 450 mA	2700 K	2120 lm	136 lm/W	048-273391◪W
	3000 K	2200 lm	142 lm/W	048-273301◪W
	3500 K	2230 lm	144 lm/W	048-273321◪W
	4000 K	2240 lm	144 lm/W	048-273311◪W
23.2 W, 36 Vf, 650 mA	2700 K	2820 lm	121 lm/W	048-273391◪W
	3000 K	2930 lm	127 lm/W	048-273301◪W
	3500 K	2970 lm	128 lm/W	048-273321◪W
	4000 K	2980 lm	128 lm/W	048-273311◪W

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 0
DALI cable ø 4 – 12 mm	105·58·30	005-255111 0


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings


COLOUR	PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	105·105·29	048-279711 7



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
traffic white	118·118·35	048-279731 7
jet black	118·118·35	048-279731 8
white aluminium	118·118·35	048-279731 G

Mounting accessories (optional)



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-269511 0

order mounting set separately

Order options

COLOUR	◪
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR	
white aluminium	RAL 9006


Electrical accessories (required)

POWER SUPPLY PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
450 mA | 21 W | non DIM	198-264 V AC	η 86 %	143·43·30	002-90766
450 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-90767
650 mA | 28 W | non DIM	198-264 V AC	η 88 %	143·43·30	002-90780
650 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-90789

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-65202 10

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-61210 30

200 - 1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA | DALI-2	176-264 V AC	η 85 %	002-90767A
650 mA | DALI-2	176-264 V AC	η 85 %	002-90789A
700 mA | DALI-2	176-264 V AC	η 85 %	002-90776A
450 mA | non DIM	198-264 V AC	η 88 %	002-90766A
650 mA | non DIM	198-264 V AC	η 88 %	002-90780A
700 mA | non DIM	198-264 V AC	η 88 %	002-90774A

2 power supplies for 2 lamps variants necessary