




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
fino a 143 lm/W
L80 / 50000 h
DALI-2, non DIM
front IP40, back IP20

Types



Colours



Set di montaggio



Distribuzione della luce



SASSO 60 round high efficient adjustable

recessed 2 lamps

EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; light insets rotatable and tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

IT Faretto a incasso rotondo; set di fissaggio con cuscinetto a sfera, senza bisogno di utensili; verniciatura; con bordo perimetrale; biemissione; inserti luminosi girevole e orientabile; emissione precisa con ottica lenticolare di alta qualità; tecnologia COB (Chip on Board) per la massima efficienza; assenza di ombre multiple; LED efficienti con alta resa cromatica



360° rotatable, 30° tiltable



glare control (UGR ≤ 16)



SASSO 60 round high efficient adjustable

30° 360° | CRI ≥ 90 | 2 SDCM | UGR ≤ 16 | cd/m² ≤ 1500 | III | DALI 1 ADDR. | IP20 IP40 | X-PERT



MEDIUM 29°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.0 W, 36 Vf, 300 mA	2700 K	2x1340 lm	134 lm/W	048-262391◪M
	3000 K	2x1400 lm	140 lm/W	048-262301◪M
	3500 K	2x1410 lm	142 lm/W	048-262321◪M
	4000 K	2x1420 lm	142 lm/W	048-262311◪M

The data values for the luminous flux of fraction may differ for specific order options by -12%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

FLOOD 32°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.0 W, 36 Vf, 300 mA	2700 K	2x1350 lm	135 lm/W	048-262391◪F
	3000 K	2x1400 lm	140 lm/W	048-262301◪F
	3500 K	2x1420 lm	142 lm/W	048-262321◪F
	4000 K	2x1430 lm	143 lm/W	048-262311◪F

The data values for the luminous flux of fraction may differ for specific order options by -13%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

WIDE FLOOD 41°-42°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.0 W, 36 Vf, 300 mA	2700 K	2x1270 lm	127 lm/W	048-262391◪W
	3000 K	2x1330 lm	133 lm/W	048-262301◪W
	3500 K	2x1340 lm	134 lm/W	048-262321◪W
	4000 K	2x1350 lm	135 lm/W	048-262311◪W


The data values for the luminous flux of fraction may differ for specific order options by -18%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

SUPER WIDE FLOOD 60°-62°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x10.0 W, 36 Vf, 300 mA	2700 K	2x1340 lm	134 lm/W	048-262391◪X
	3000 K	2x1390 lm	139 lm/W	048-262301◪X
	3500 K	2x1410 lm	141 lm/W	048-262321◪X
	4000 K	2x1410 lm	141 lm/W	048-262311◪X

The data values for the luminous flux of fraction may differ for specific order options by -14%. Luminous flux value refers to colour traffic white. 2 insets necessary, order code only applies to 1 inset

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX


TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253111 10
DALI cable ø 4 – 12 mm	105·58·30	005-255111 10

Linect®-Ready

Order options

COLOUR ◪	
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L·W·H (mm)	ORDER CODE
147·80·21	048-269831


Electrical accessories (required)

POWER SUPPLY 300 mA, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
non DIM	η 84 %	85·40·22	002-90771
DALI-2	η 87 %	165·29·21	002-90790

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-6520210

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-6121030

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10–40 V SELV

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA | 15 W | DALI-2	η 87 %	002-90790A
250 mA | 15 W | DALI-2	η 87 %	002-90748A
300 mA | 15 W | non DIM	η 84 %	002-90771A
250 mA | 10 W | non DIM	η 80 %	002-90742A

2 power supplies for 2 lamps variants necessary

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA	η 87 %	185·30·21	002-90770
250 mA	η 87 %	185·30·21	002-90747

2 power supplies for 2 lamps variants necessary

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8
white aluminium RAL 9006	G